





14.1. 10 kV kabelių ilgalaikės leistinosios srovės

Laidininko medžiaga	Varinis		Aliuminis	
Kabelio žymėjimas	N2XS _Y , N2XS ₂ Y, N2XS(F)2Y		NA2XS _Y , NA2XS ₂ Y, NA2XS(F)2Y	
Klojimo būdas				
Laidininko skerspjūvis mm ²	Srovė (A) žemėje (20°C)			
25	157	179		
35	187	212		
50	220	249	171	194
70	268	302	208	236
95	320	359	248	281
120	363	405	283	318
150	405	442	315	350
185	456	493	357	394
240	526	563	413	452
300	591	626	466	506
400	662	675	529	558
500	744	748	602	627
3x1x50RM/16			171	
3x1x70RM/16			208	
3x1x95RM/16			248	
3x1x120RM/16			283	
3x1x150RM/25			315	
3x1x185RM/25			357	
3x1x240RM/25			413	
3x50SE/16			163	
3x70SE/16			201	
3x95SE/16			239	
3x120SE/16			273	
3x150SE/25			305	
3x185SE/25			346	
Laidininko skerspjūvis mm ²	Srovė (A) ore (30°C)			
25	163	194		
35	197	235	153	182
50	236	282	183	219
70	294	350	228	273
95	358	426	278	333
120	413	491	321	384
150	468	549	364	432
185	535	625	418	496
240	631	731	494	583
300	722	831	568	666
400	827	920	660	755
500	949	1043	767	868
3x1x50RM/16			183	
3x1x70RM/16			228	
3x1x95RM/16			278	
3x1x120RM/16			321	
3x1x150RM/25			364	
3x1x185RM/25			418	
3x1x240RM/25			494	
3x50SE/16			169	
3x70SE/16			212	
3x95SE/16			257	
3x120SE/16			297	
3x150SE/25			336	
3x185SE/25			386	