

Product data sheet

Specifications



Renova - single socket outlet - 2P + E - 16 A - 250 V - white

WDE011103

Main

Range	Renova
Product or component type	Socket-outlet
Device presentation	Mechanism with fixing frame
Quantity per set	Set of 5
Product compatibility	To be completed with Renova frame

Complementary

Socket number	1
Device mounting	Flush
Outlet poles configuration	2P + E
Outlet standard description	Side earth
Outlet standard	Schuko
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Colour tint	White (RAL 9010)
Connections - terminals	Screwless terminals
Clamping connection capacity	1 x 1.5...2 x 2.5 mm² for solid cable(s) 1 x 1.5...2 x 2.5 mm² for solid stranded cable(s)
Material	PC/ABS
Fixing mode	By screws and claws
Diameter	71 mm
Embedding depth	28 mm
Projecting depth	15 mm

Environment

Standards	DIN VDE 0620-1 IEC 60884-1 SS 4280834 SFS 5610:2004
Product certifications	FIMKO SEMKO
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	67 g
Package 1 Height	4 cm
Package 1 width	7.1 cm
Package 1 Length	7.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	394 g
Package 2 Height	8.5 cm
Package 2 width	8.5 cm
Package 2 Length	22.5 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Weight	6.77 kg
Package 3 Height	32.5 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins