



# Altira - 1 SO - 2P+E with shutters - side earth - aluminium

ALB46282

① Discontinued on: 14 July 2021

• End-of-service on: 14 July 2021

① Discontinued

|   |   | •  |
|---|---|----|
| M | a | ın |

| Range                          | Altira                    |
|--------------------------------|---------------------------|
| Product or component type      | Socket-outlet             |
| Range compatibility            | fixing frame fixing frame |
| Device presentation            | Mechanism                 |
| Number of power socket outlets | 1 x 2P + E, German        |
| Outlet standard description    | Side earth                |
| Socket additional information  | Shuttered                 |
| Colour tint                    | Aluminium                 |

| Complementary                |   |
|------------------------------|---|
| Product destination          | Fixing frames   |
| Range compatibility          | OptiLine 45 OptiLine 70 with Altira adaptor   |
| Ground lug position          | Slanted 45° position  |
| Rated current                | 16 A at 250 V AC 50/60 Hz   |
| Number of modules            | 2 modules   |
| Fixing mode                  | Clip-in   |
| Connections - terminals      | Screwless terminals   |
| Clamping connection capacity | 4 x 1.54 x 2.5 mm² for rigid cable(s)<br>4 x 1.54 x 2.5 mm² for solid stranded cable(s) |
| Material                     | PC: mechanism cover   |
| Surface treatment            | Untreated   |
| Surface finish               | Satin   |
| Standards                    | EN 62262<br>IEC 60884-1<br>EN 60529<br>NF C 61-314                                      |
| Height                       | 45 mm   |
| Width                        | 45 mm   |
| Depth                        | 39 mm   |

#### **Environment**

| Ambient air temperature for operation | 550 °C  |
|---------------------------------------|---|
| Ambient air temperature for storage   | -1560 °C  |
| IK degree of protection               | IK02  |
| IP degree of protection               | IP20  |
| Environmental characteristic          | Window-cleaning fluid Acetone Alcohol Bleach Petrol Hydrogen peroxide (H2O2) Liquid soap UV resistant Oil |

## **Packing Units**

| Unit Type of Package 1       | PCE       |
|------------------------------|-----------|
| Number of Units in Package 1 | 1         |
| Package 1 Weight             | 32 g      |
| Package 1 Height             | 4.2 cm    |
| Package 1 width              | 4.5 cm    |
| Package 1 Length             | 4.5 cm    |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 10        |
| Package 2 Weight             | 397 g     |
| Package 2 Height             | 9 cm      |
| Package 2 width              | 9 cm      |
| Package 2 Length             | 22 cm     |
| Unit Type of Package 3       | S04       |
| Number of Units in Package 3 | 280       |
| Package 3 Weight             | 11.882 kg |
| Package 3 Height             | 30 cm     |
| Package 3 width              | 40 cm     |
| Package 3 Length             | 60 cm     |

## Offer Sustainability

| EU RoHS Directive          | Compliant EU RoHS Declaration  |
|----------------------------|--|
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| RoHS exemption information | Yes  |
| China RoHS Regulation      | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure   | Product Environmental Profile  |

## **Contractual warranty**

| Warranty | 18 months |  |
|----------|-----------|--|
|          |           |  |
|          |           |  |

## Recommended replacement(s)

ALB46282 is replaced by the following product range:

