

Product data sheet

Specifications



Renova Surface Switch 2x two-way with screwless terminals black

WDE015926

Main

Range	Renova
Product or component type	Switch
Device application	Light control
Device presentation	Complete product
Colour	Black (NCS S 9000-N)
Quantity per set	Set of 5
Switch function	Double 2-way

Complementary

Technology type	Electromechanical
Rated current	16 AX
[Ue] rated operational voltage	250 V AC
Connections - terminals	Screwless terminals
Number of loop terminals	0.0
Clamping connection capacity	1 x 1.5...2 x 2.5 mm² for solid cable(s) 1 x 1.5...2 x 2.5 mm² for solid stranded cable(s)
Device mounting	Surface
Number of rocker	2
Switch pattern	[6+6]
Actuator	Rocker
Material	PC: cover PC 10 % GF: bottom-plate PC/ABS: rocker
Surface finish	Cover plate: glossy Cover frame: matt
Fixing mode	By screw
Diameter	70.0 mm
Embedding depth	0.0 mm
Projecting depth	27.0 mm
IP degree of protection	IP20 also with visual parts removed IP21 when cable is coming from below
Product certifications	CE FIMKO

	NEMKO SEMKO
Standards	EN 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	64 g
Package 1 Height	3.6 cm
Package 1 width	6.8 cm
Package 1 Length	6.9 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	366 g
Package 2 Height	8.8 cm
Package 2 width	8.6 cm
Package 2 Length	22.8 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	4.882 kg
Package 3 Height	30.2 cm
Package 3 width	28.8 cm
Package 3 Length	39.2 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins