

Product data sheet

Specifications



Renova Surface Double Socket-Outlet Schuko with screwless terminals black

WDE015996

Main

Range	Renova
Product or component type	Socket-outlet
Device presentation	Complete product
Quantity per set	Set of 10

Complementary

Socket number	2
Device mounting	Surface
Outlet poles configuration	2P + E
Outlet standard description	Side earth
Outlet standard	Schuko
Rated current	16 A
Cover type	Full cover plate
[Ue] rated operational voltage	250 V AC
Colour tint	Black (NCS S 9000-N)
Connections - terminals	Screwless terminals
Number of loop terminals	2.0
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² for solid cable(s) 1 x 1.5...2 x 2.5 mm ² for solid stranded cable(s)
Material	PC (polycarbonate): cover frame PC 10 % GF: bottom-plate
Fixing mode	By screws: insert By screws: cover frame
Width	70.0 mm
Height	111.0 mm
Embedding depth	0.0 mm
Projecting depth	43.0 mm

Environment

Standards	DIN VDE 0620-1 IEC 60884-1 NEK 502 SFS 5610
-----------	--

Product certifications	FIMKO NEMKO SEMKO CE
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	98 g
Package 1 Height	4.5 cm
Package 1 width	7 cm
Package 1 Length	11 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.14 kg
Package 2 Height	11.8 cm
Package 2 width	18 cm
Package 2 Length	25.6 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Weight	12.098 kg
Package 3 Height	29.8 cm
Package 3 width	39.2 cm
Package 3 Length	59.6 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins