

# Gaminio duomenų lentelė

Specifikacijos



## Easy UPS 3S 30 kVA 400V 3:3 UPS, 4 internal 7Ah modular battery strings

E3SUPS30KHB2

### Apžvalga

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pristatymas       | Easy-to-install, easy-to-operate, easy-to-maintain, and easy-to-service 30 kVA, 400V 3-phase UPS. With advanced product features, competitive specifications, and robust electrical design, the Easy UPS 3S UPS makes business continuity easy for small and medium data centers and electrical rooms. Includes dust filter and conformance-coated boards for harsh environments, and 4 internal 7Ah modular battery strings. |
| Pristatymo laikas | Usually Ships within 6 Weeks                                                                                                                                                                                                                                                                                                                                                                                                  |

### Main

|                      |                                   |
|----------------------|-----------------------------------|
| Main Input Voltage   | 3 phases                          |
| Other Input Voltage  | 380 V<br>415 V                    |
| Main Output Voltage  | 400 V 3 phases                    |
| Other Output Voltage | 380 V<br>415 V                    |
| Rated power in W     | 30000 W                           |
| Rated power in VA    | 30000 VA                          |
| Battery type         | VRLA                              |
| Provided equipment   | Dust filter<br>Installation guide |

### Physical

|                |                 |
|----------------|-----------------|
| Colour         | White RAL 9003) |
| Height         | 140 cm          |
| Width          | 50 cm           |
| Depth          | 96,9 cm         |
| Net weight     | 584 kg          |
| USB compatible | Yes             |

### Input

|                                 |                             |
|---------------------------------|-----------------------------|
| Maximum input current           | 55 A                        |
| Input harmonic distortion       | Less than 3 % for full load |
| Load power factor               | 0.9 leading to 0.9 lagging  |
| Input Power Factor at Full Load | 0,99                        |
| Input voltage limits            | 304...477 V                 |

|                   |            |
|-------------------|------------|
| Network frequency | 45...65 Hz |
|-------------------|------------|

## Output

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| Maximum configurable power in VA | 30000 VA                                    |
| Maximum configurable power in W  | 30000 W                                     |
| Output frequency                 | 50 Hz sync to mains<br>60 Hz sync to mains  |
| Harmonic distortion              | Less than 3 %                               |
| Output harmonic distortion       | < 3% linear load                            |
| Output voltage tolerance         | +/- 1.5 %                                   |
| UPS type                         | Double conversion online                    |
| Additional information           | UPS weight does not include battery weight. |

## Conformance

|                        |                                                                       |
|------------------------|-----------------------------------------------------------------------|
| Product certifications | CE<br>EAC<br>RCM                                                      |
| Standards              | IEC 62040-1-1<br>IEC 62040-2<br>IEC 62040-3<br>IEC 62040-4<br>ISTA 2B |

## Environmental

|                                       |                         |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C               |
| Relative humidity                     | 0...95 % non-condensing |
| Operating altitude                    | 0...3333 ft             |
| Ambient air temperature for storage   | -15...40 °C             |
| Storage Relative Humidity             | Non-condensing 0...95 % |
| Storage altitude                      | 0,00...15240,00 m       |
| Acoustic level                        | 63 dBA                  |
| Heat dissipation                      | 1410 Btu/h              |
| IP degree of protection               | IP20                    |

## Batteries & Runtime

|                                |       |
|--------------------------------|-------|
| Battery voltage                | 240 V |
| Maximum short-circuit current  | 10 kA |
| Number of battery filled slots | 4     |
| Number of battery free slots   | 0     |

## Pakavimo vienetai

|                    |          |
|--------------------|----------|
| 1 pakuotės svoris  | 638 kg   |
| 1 pakuotės aukštis | 164 cm   |
| 1 pakuotės plotis  | 68,3 cm  |
| 1 pakuotės ilgis   | 111,4 cm |

Offer Sustainability

|                                |                                                                                                                                               |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| REACH direktyva                | <a href="#">REACH deklaracija</a>                                                                                                             |
| REACH be SVHC                  | Taip                                                                                                                                          |
| ES RoHS direktyva              | Aktyvus laikymasis (gaminys nepatenka į ES RoHS teisinę aprėptį)<br><a href="#">ES RoHS deklaracija</a>                                       |
| Be gyvsidabrio                 | Taip                                                                                                                                          |
| RoHS išimčių informacija       | <a href="#">Taip</a>                                                                                                                          |
| Kinijos RoHS direktyva         | <a href="#">Kinijos RoHS deklaracija</a><br>Produktas neįeina į Kinijos RoHS apimtį. Medžiagų deklaracija pateikiama jūsų informacijai.       |
| WEEE                           | Šį produktą Europos Sąjungos rinkose reikia utilizuoti perduodant į specialias surinkimo vietas ir negalima išmesti su buitinėmis atliekomis. |
| Optimizuotas energijos našumas | Energijos našumą užtikrinantis produktas                                                                                                      |

Contractual warranty

|           |                                                                   |
|-----------|-------------------------------------------------------------------|
| Garantija | 1 year on-site repair or replace with factory authorized Start-Up |
|-----------|-------------------------------------------------------------------|