

Gaminio duomenų lentelė

Specifikacijos



Easy UPS 3S 40 kVA 400V 3:3 UPS, 4 internal 7Ah modular battery strings

E3SUPS40KHB2

Apžvalga

Pristatymas	Easy-to-install, easy-to-operate, easy-to-maintain, and easy-to-service 40 kVA, 400V 3-phase UPS. With advanced product features, competitive specifications, and robust electrical design, the Easy UPS 3S UPS makes business continuity easy for small and medium data centers and electrical rooms. Includes dust filter and conformance-coated boards for harsh environments, and 4 internal 7Ah modular battery strings.
Pristatymo laikas	Usually Ships within 6 Weeks

Main

Main Input Voltage	3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in W	40000 W
Rated power in VA	40000 VA
Battery type	VRLA
Provided equipment	Dust filter Installation guide

Physical

Colour	White RAL 9003)
Height	140 cm
Width	50 cm
Depth	96,9 cm
Net weight	590 kg
USB compatible	Yes

Input

Maximum input current	73 A
Input harmonic distortion	Less than 3 % for full load
Load power factor	0.9 leading to 0.9 lagging
Input Power Factor at Full Load	0,99
Input voltage limits	304...477 V

Network frequency	45...65 Hz
-------------------	------------

Output

Maximum configurable power in VA	40000 VA
Maximum configurable power in W	40000 W
Output frequency	50 Hz sync to mains 60 Hz sync to mains
Harmonic distortion	Less than 3 %
Output harmonic distortion	< 3% linear load
Output voltage tolerance	+/- 1.5 %
UPS type	Double conversion online
Additional information	UPS weight does not include battery weight.

Conformance

Product certifications	CE EAC RCM
Standards	IEC 62040-1-1 IEC 62040-2 IEC 62040-3 IEC 62040-4 ISTA 2B

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0,00...15240,00 m
Acoustic level	63 dBA
Heat dissipation	1880 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery voltage	240 V
Maximum short-circuit current	10 kA
Number of battery filled slots	4
Number of battery free slots	0

Pakavimo vienetai

1 pakuotės svoris	643 kg
1 pakuotės aukštis	164 cm
1 pakuotės plotis	68,3 cm
1 pakuotės ilgis	111,4 cm

Offer Sustainability

REACH direktyva	REACH deklaracija
REACH be SVHC	Taip
ES RoHS direktyva	Aktyvus laikymasis (gaminys nepatenka į ES RoHS teisinę aprėptį) ES RoHS deklaracija
Be gyvsidabrio	Taip
RoHS išimčių informacija	Taip
Kinijos RoHS direktyva	Kinijos RoHS deklaracija Produktas neįeina į Kinijos RoHS apimtį. Medžiagų deklaracija pateikiama jūsų informacijai.
WEEE	Šį produktą Europos Sąjungos rinkose reikia utilizuoti perduodant į specialias surinkimo vietas ir negalima išmesti su buitinėmis atliekomis.
Optimizuotas energijos našumas	Energijos našumą užtikrinantis produktas

Contractual warranty

Garantija	1 year on-site repair or replace with factory authorized Start-Up
-----------	---