Technical Datasheet

PSKU18 clutch, black



- Material connector housing PP (Polypropylen)
- Rated voltage: 250V AC
- Rated current: 16A AC
- Type: acc. DIN 49440
- Conductor cross-section of the connection cable 0.75 to 2.5mm²
- Terminal type: screw terminal; reconnectable
- Number of poles: 2 + PE
- Protective contact: Version as a side protection contact acc. DIN 49440
- permissible outer diameter of the connection cable: 10.4 mm
- Strain relief: Pressure piece with 2 screws
- Torque for connection screws: 0.4 Nm
- Torque for strain relief: 0.5 Nm
- Sheath stripping length: 40 mm to 45 mm
- Wire stripping length: 7 mm
- Test mark: VDE, ÖVE
- Certified according to DIN ISO 9001
- Hint:
  - When connecting the cable , make sure that the wire insulation is not clamped
  - Before closing the housing, check the fixed position of the cables in the connection terminals and make sure that no cable is clamped between the housing parts.

Information

Art.-No.	ID-No.	Type	VPE	Colour
05105822	056495	PSKU18	1	black

Errors and technical changes excepted. Reproduction and any electronic reproduction only with our written permission.
All rights reserved. As of 2021. © PROTEC.class/PROTEC.net