



Shunt release, 12-110V, 1HP

Part no. ZP-ASA/24
Catalog No. 248438

EL-Nummer (Norway) 0001609470

Delivery program

| | | | |
|----------------------------|--|--|---|
| Basic function | | | Accessories for miniature circuit-breaker Accessories for combined residual-current/power circuit-breakers |
| Basic function accessories | | | Shunt release |
| Application | | | Switchgear for industrial and advanced commercial applications |
| Product range | | | Accessory |
| Side mounting | | | for fitting on left to: FAZ, FRBmM-1N, Z-MS |
| Contact sequence | | | |

Technical data

Design verification as per IEC/EN 61439

| | | | |
|--|----|--|----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | °C | | -5 |
| Operating ambient temperature max. | °C | | 40 |

Technical data ETIM 7.0

| | | | |
|---|--|---|---|
| Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecI@ss10.0.1-27-14-35-02 [AKE327013]) | | | |
| Device fitting | | | Other |
| Additional equipment | | | Shunt release (for power circuit breaker) |
| Attached at delivery | | | No |
| Assembly width (TE) | | | 1 |
| Number of contacts as normally open contact | | | 1 |
| Number of contacts as normally closed contact | | | 1 |
| Number of contacts as change-over contact | | | 0 |
| Number of fault-signal switches | | | 0 |
| Rated switch current | | A | 0 |
| Rated voltage | | V | 24 |
| Voltage type for actuating | | | AC |
| With auto test for earth leakage function | | | No |
| Suitable for max. number of poles main contact unit (total) | | | 1 |
| Suitable for max. current main contact unit | | A | 15 |

Dimensions

