GRUS S LED1X1500 C314 T740 L30 • 1021132




Product:	Grus S LED1x1500 C314 T740 L30	
Order code:	1021132	
Family:	Grus S LED	
Product group:	Outdoor accent lighting	
GENERAL D	ATA	
Description:	Surface mounted accent LED lumin	aire
	Light distribution type: direct	
	Optical system: lenses, tempered g Housing: aluminium	lass diffuser, impact resistant
	Colour: dark grey (RAL7043)	
Instalation:	On the horizontal or vertical surface. Cable, 0.3m, 3x0.75mm2	
Environment	Outdoor	
Application	public space, facade illumination	


ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	10,7
Power factor:	>0,5	Control gear:	ECG on/off
Connection:	Cable, 0.3m, 3x0.75mm2		
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	1484	System efficacy, Im/W:	139
CRI (Ra):	70+	ССТ, К:	4000
SDCM:	5	Light Distribution:	Symmetrical medium beam (31°75°)
Distribution Type:	Direct	Beam angle, °:	32
LED lifetime, h:	50000/L70B50		
TECHNICAL DATA			
Net weight, kg:	0.9	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0018	Pallet quantity, pcs:	470
Dimensions, mm:	120x120x90		
STANDARDS			
Operating temperature range, °C:	-25+40 C	Protection class IEC:	I
Ingress protection code:	IP65	Mechanical impact resistance:	IK08
EEC:	С	Certificates:	CE, UKCA, RoHS
Warranty:	3 years		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-05-17
NORTHCLIFFE LIGHTING, UAB
Raudondvario pl. 101, LT-47184 Kaunas, Lithuania
info@northcliffe.org
www.northcliffe.org