

ANDROMEDA P LED1X2100 D525 T830 OP • 1022752




| Product: | Andromeda P LED1x2100 D525 T830 OP |
|---------------|------------------------------------|
| Order code: | 1022752 |
| Family: | Andromeda P LED |
| Product group | : Downlights |

GENERAL DATA


| Description: | Recessed mounted low-cost LED downlight Light distribution type: direct Optical system: opal polycarbonate diffuser Housing: polycarbonate Colour: white | | |
|--------------|--|--|--|
| Instalation: | In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm2 | | |
| Environment | Indoor | | |
| Application | office, education, corridor, retail, public place, showroom, hotel, bathroom | | |
| | | | |

ELECTRICAL DATA

| Mains voltage: | 220-240V, 50/60Hz | System power*, W: | 20 |
|-------------------------------------|------------------------------|---|------------------------------------|
| Power factor: | >0,8 | Control gear: | ECG on/off |
| Connection: | Push-in terminal, 2x1x1.5mm2 | | |
| LIGHTING DATA | | | |
| Light source and cap, W: | LED | Light source included: | yes |
| Luminaire output*, lm(ta+25°C): | 1960 | System efficacy, Im/W: | 98 |
| CRI (Ra): | 80+ | ССТ, К: | 3000 |
| SDCM: | 5 | Light Distribution: | Symmetrical wide beam (76 125) |
| Distribution Type: | Direct | Beam angle, °: | 105 |
| LED lifetime, h: | 40000/L70B50 | | |
| TECHNICAL DATA | | | |
| Net weight, kg: | 0.53 | Mounting holes/cut-out dimensions, mm: | d200 |
| Quantity in package, pcs: | 1 | Packaging volume, m3/pcs: | 0.007 |
| Pallet quantity, pcs: | 120 | | |
| Dimensions, mm: | 244x244x95 | | |
| STANDARDS | | | |
| Operating temperature range, °C: | ta 0+35 | Protection class IEC: | II |
| Ingress protection code: | IP44 | Mechanical impact resistance: | IK04 |
| EEC: | E | Certificates: | CE, RoHS |
| Warranty: | 3 years | | |



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-05-18
NORTHCLIFFE LIGHTING, UAB Raudondvario pl. 101, LT-47184 Kaunas, Lithuania info@northcliffe.org
www.northcliffe.org