

PAVO P LED1X2000 D517 T840 • 1022741

220-240V, 50/60Hz



Product: Pavo P LED1x2000 D517 T840
Order code: 1022741
Family: Pavo P LED
Product group: Diffuser and wall luminaires

GENERAL DATA

Description: Surface mounted LED luminaire

Light distribution: direct

Optical system: opal PMMA diffuser

Housing: steel

Colour: white (RAL 9003)

System power*, W:

Instalation: On the ceiling or wall. Screw terminal, 3x1.5mm2

Environment Indoor

Application office, education, corridor, public place, hotel, staircase, bathroom, healthcare


22

ELECTRICAL DATA


Mains voltage:

a ro.lage.	220 2 1017 507 501.12	-, pone. ,	
Power factor:	>0,90	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Screw terminal, 3x1.5mm2
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	2200	System efficacy, lm/W:	100
CRI (Ra):	80+	сст, к:	4000
SDCM:	5	Light Distribution:	Symmetrical wide beam (76°125°)
Distribution Type:	Direct	Beam angle, °:	118
UGR index:	≤22	LED lifetime, h:	40000/L70B50
TECHNICAL DATA			
Net weight, kg:	0.9	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0162	Pallet quantity, pcs:	40
Dimensions, mm:	410x410x115		
STANDARDS			
Operating temperature range, °C:	ta -15+35	Protection class IEC:	I
Ingress protection code:	IP44	Mechanical impact resistance:	IK02
EEC:	E	Certificates:	CE, RoHS
Warranty:	3 years		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-05-18 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org