

## ANDROMEDA P LED1X1000 D523 T840 OP • 1022747

220-240V, 50/60Hz



Product:	:: Andromeda P LED1x1000 D523 T840 O	
Order code:	1022747	
Family:	Andromeda P LED	
Product group:	"Downlight" tipo šviestuvai	

System power\*, W:

### GENERAL DATA

Description:	Recessed mounted low-cost LED downlight Light distribution type: direct Optical system: opal polycarbonate diffuser Housing: polycarbonate Colour: white		
Instalation:	In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm2		
Environment	Indoor		
Application	office, education, corridor, retail, public place, showroom, hotel, bathroom		


10

#### **ELECTRICAL DATA**


Mains voltage:

rianis voitagei	220 2 101, 30,00112	System ponter , m	10
Power factor:	>0,6	Control gear:	ECG on/off
Connection:	Push-in terminal, 2x1x1.5mm2		
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	980	System efficacy, lm/W:	98
CRI (Ra):	80+	сст, к:	4000
SDCM:	5	Light Distribution:	Symmetrical wide beam (76125 )
Distribution Type:	Direct	Beam angle, °:	105
LED lifetime, h:	40000/L70B50		
TECHNICAL DATA			
Net weight, kg:	0.16	Mounting holes/cut-out dimensions, mm:	d95
Quantity in package, pcs:	1	Packaging volume, m3/pcs:	0.0014
Pallet quantity, pcs:	640		
Dimensions, mm:	113x113x73		
STANDARDS			
Operating temperature range, °C:	ta 0+35	Protection class IEC:	II
Ingress protection code:	IP44	Mechanical impact resistance:	IK04
EEC:	E	Certificates:	CE, RoHS
Warranty:	3 years		

#### Technical drawing (.jpg)



# Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data:  $\pm 10\%$ . Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-05-19 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org