

## PUPIS P LED1X500 D541 T730 OP • 1023332



Product:	Pupis P LED1x500 D541 T730 OP		
Order code:	1023332		
Family:	Pupis P LED		
Product group:	p: Plastikiniai šviestuvai		

## GENERAL DATA

**Description:** Surface mounted plastic LED luminaire

Light distribution type: direct

Optical system: opal polycarbonate diffuser, impact resistant

Housing: polycarbonate

Colour: white

**Instalation:** On the ceiling or walls. Screw terminal, 2x1.5mm2


**Environment** Indoor

**Application** office, education, corridor, public place, staircase, bathroom, healthcare


## **ELECTRICAL DATA**

Mains voltage:	220-240V, 50/60Hz	System power*, W:	5
Power factor:	>0,55	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Screw terminal, 2x1.5mm2
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	500	System efficacy, lm/W:	100
CRI (Ra):	70+	сст, к:	3000
SDCM:	5	Light Distribution:	Wide-wide beam (C0-C180 plane 76°125°, C90-C270 plane 76°125°)
Distribution Type:	Direct	Beam angle, °:	110x121
LED lifetime, h:	40000/L70B50		
TECHNICAL DATA			
Net weight, kg:	0.18	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0009	Pallet quantity, pcs:	1020
Dimensions, mm:	171x71x45		
STANDARDS			
Operating temperature range, °C:	ta -15+35	Protection class IEC:	II
Ingress protection code:	IP65	Mechanical impact resistance:	IK08
EEC:	E	Certificates:	CE, RoHS
Warranty:	3 years		

Technical drawing (.jpg)



## Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data:  $\pm 10\%$ . Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-05-19 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org