

CETUS P LED1X1200 D671 T830 OP • 1024015



Product:	Cetus P LED1x1200 D671 T830 OP		
Order code:	1024015		
Family:	Cetus P LED		
Product group:	Plastikiniai šviestuvai		

GENERAL DATA

Description: Surface mounted plastic LED luminaire

Light distribution type: direct

Optical system: opal polycarbonate diffuser, impact resistant

Housing: polycarbonate

Colour: white

Instalation: On the ceiling or wall. Screw terminal, 2x1.5mm2


Environment Indoor

 $\textbf{Application} \quad \text{office, education, corridor, public place, staircase, bathroom, healthcare} \\$


ELECTRICAL DATA

Technical drawing (.jpg)

Mains voltage:	220-240V, 50/60Hz	System power*, W:	12
Power factor:	>0,55	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Screw terminal, 2x1.5mm2
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	1080	System efficacy, lm/W:	90
CRI (Ra):	80+	сст, к:	3000
SDCM:	5	Light Distribution:	Symmetrical wide beam (76°125°)
Distribution Type:	Direct	Beam angle, °:	126
LED lifetime, h:	40000/L70B50		
TECHNICAL DATA			
Net weight, kg:	0.19	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0022	Pallet quantity, pcs:	390
Dimensions, mm:	160x160x63		
STANDARDS			
Operating temperature range, °C:	ta -15+35	Protection class IEC:	II
Ingress protection code:	IP65	Mechanical impact resistance:	IK08
EEC:	F	Certificates:	CE, RoHS
Warranty:	3 years		



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-05-19 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org