

INDUS P LED1X1650 D502 T840 1G • 1024090

Product:	Indus P LED1x1650 D502 T840 1G
Order code:	1024090
Family:	Indus P LED
Product group:	Plastikiniai šviestuvai

GENERAL DATA

Description:	Surface mounted plastic LED luminaire Light distribution type: direct Optical system: opal acrylic diffuser, UV resistant Housing: thermoplastic Colour: white
Installation:	On the ceiling or wall. Push-in terminal, 2x2x2.5mm ²
Environment	Indoor/outdoor with roof
Application	office, education, corridor, public place, hotel, staircase, bathroom, healthcare, parking area

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	13.5
Power factor:	>0,95	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Push-in terminal, 2x2x2.5mm ²

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	1539	System efficacy, lm/W:	114
CRI (Ra):	80+	CCT, K:	4000
SDCM:	3	Light Distribution:	Symmetrical wide beam (76°...125°)
Distribution Type:	Direct	Beam angle, °:	112
UGR index:	≤22	LED lifetime, h:	50000/L80B50


TECHNICAL DATA

Net weight, kg:	1.1	Quantity in package, pcs:	1
Packaging volume, m³/pcs:	0.0106	Pallet quantity, pcs:	80
Dimensions, mm:	295x295x100		


STANDARDS

Operating temperature range, °C:	ta -15...+35	Protection class IEC:	II
Ingress protection code:	IP65	Mechanical impact resistance:	IK08
EEC:	E	Certificates:	CE, RoHS
Warranty:	3 years		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note: Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification