

DISC LED1X21000 E928 T840 • 1102583

Product:	Disc LED1x21000 E928 T840
Order code:	1102583
Family:	Disc LED
Product group:	Aukštų patalpų šviestuvai

GENERAL DATA

Description:	Suspended high-bay low-cost LED luminaire Light distribution type: direct Optical system: lens, 90°, impact resistance Housing: aluminium Colour: black (RAL 9011)
Installation:	Suspended (suspension hook included). Cable, 0.5m, 3x1.0mm2
Environment	Indoor
Application	industry, warehouse, hall

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	140
Power factor:	>0,9	Control gear:	ECG on/off
Surge protection (L to N), kV:	5	Surge protection (L/N to PE), kV:	10
Connection:	Cable, 0.3m, 3x1.0mm2		

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	21589	System efficacy, lm/W:	151
CRI (Ra):	80+	CCT, K:	4000
SDCM:	6	Light Distribution:	Symmetrical wide beam (76 ...125)
Distribution Type:	Direct	Beam angle, °:	71
LED lifetime, h:	50000/L70B50	Ripple current (≤120 Hz), %:	≤3


TECHNICAL DATA

Net weight, kg:	3	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0169	Pallet quantity, pcs:	96
Dimensions, mm:	336x336x127		


STANDARDS

Operating temperature range, °C:	ta -20...+40	Protection class IEC:	I
Ingress protection code:	IP65	Mechanical impact resistance:	IK08
EEC:	C	Certificates:	CE, RoHS
Warranty:	3 years		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-05-19 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org