# **PHILIPS** Lighting



# LED Bollard II

## BCP150 LED150/WW PSU 220-240V 7043

LED module 340 lm - Warm white - Power supply unit - 220 to 240 V

People want to create a pleasant atmosphere around their property – something that will catch visitors' attention, make them feel good and want to come back again. They would like to be able to create an appealing ambience with optimized-quality lighting at minimum cost. Combining reliable low-power LEDs and an integrated driver, the robustly designed LED Bollard II delivers an affordable LED lighting solution to meet your landscaping needs.

#### **Product data**

General Information	
Number of light sources	1 pc
Lamp family code	LED3.4 [ LED module 340 lm]
Light source color	Warm white
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optical cover/lens type	Polycarbonate bowl/cover UV-resistant
Embedded control	-
Control interface	-
Connection	Screw connection block
Cable	Cable without plug 3-pole
Protection class IEC	Safety class I
CE mark	CE mark
ENEC mark	-
RAL color	Traffic gray B (7043)

Constant light output	No
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Power Factor (Min)	0.4
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Aluminum
Optical cover/lens material	Polycarbonate
Overall height	500 mm
Overall diameter	180 mm
Color	Gray

### LED Bollard II

Approval and Application	
Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [ 20 J vandal-resistant]
Initial Performance (IEC Comp	liant)
Initial luminous flux (system flux)	200 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	28.57 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>70
Initial input power	7 W
Power consumption tolerance	+/-10%

Product Data	
Full product code	871016329887000
Order product name	BCP150 LED150/WW PSU 220-240V 7043
EAN/UPC - Product	8710163298870
Order code	911401691902
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401691902
Net Weight (Piece)	1.319 kg




#### **Application Conditions**

Ambient temperature range

-20 to +40 °C

#### Dimensional drawing





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2019, December 30 - data subject to change