OVE Austrian Electrotechnical Association

Eschenbachgasse 9 | 1010 Wien | Austria

ZVR: 327279890 | www.ove.at

OVE Certification

Kahlenberger Str. 2A | 1190 Wien | Austria T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at



Page 1 of 15

ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark



Certificate No.: Valid from: 2023 03 15 43-152-16

until: 2024 05 17

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

PC Electric Ges.m.b.H. Company:

Diesseits 145

4973 St. Martin im Innkreis

Austria

Product: Socket outlets for industrial purposes

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s):: 3722-1860/23

Österreichischer Verband für Elektrotechnik


Head of OVE Certification

Digitally signed by T. Neumayer Email=t.neumayer@ove.at

Dipl.-Ing. T. Neumayer

Wien, 2023 03 15









Date: 2023 03 15 Page 2 of 15

Manufacturer:

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Factory location(s):

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01 ÖVE/ÖNORM EN 60309-2:2013-03-01 EN IEC 60309-1:2022 EN IEC 60309-2:2022 IEC 60309-1:2021 IEC 60309-2:2021

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

Tradomark:

Product: Socket outlets for industrial purposes

| Rating: | тацетак: |
|---|-------------------------------|
| 133 Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist | PCE / ELCEE / SIROX / METECEE |
| 134 Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist | PCE / ELCEE / SIROX / METECEE |



Typo docionation:





Date: 2023 03 15 Page 3 of 15

135 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

1335 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

1336 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

1345 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

1346 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

1355 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

1356 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 for wall mounting see typelist







Date: 2023 03 15 Page 4 of 15

333 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 straight design see typelist

334 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 straight design see typelist

335 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 straight design see typelist

3335 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 straight design see typelist

3336 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 straight design see typelist

3345 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 straight design see typelist

3346 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 straight design see typelist





Date: 2023 03 15 Page 5 of 15

3355 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 straight design see typelist

3356 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 straight design see typelist

433 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 sloping design see typelist

434 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 sloping design see typelist

435 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 sloping design see typelist

4335 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 sloping design see typelist

4336 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 sloping design see typelist





Date: 2023 03 15 Page 6 of 15

4345 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 sloping design see typelist

4346 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 sloping design see typelist

4355 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 sloping design see typelist

4356 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 sloping design see typelist

1337 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

1347 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 oder IP 66/IP 67 for wall mounting see typelist

1357 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 for wall mounting see typelist





Date: 2023 03 15 Page 7 of 15

13375 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

13376 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

13475 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

13476 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

13575 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

13576 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 for wall mounting see typelist

1331 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 for wall mounting see typelist







Date: 2023 03 15 Page 8 of 15

1341 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 for wall mounting see typelist

1351 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 for wall mounting see typelist

13351 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 for wall mounting see typelist

13361 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 for wall mounting see typelist

13451 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 for wall mounting see typelist

13461 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 for wall mounting see typelist

13551 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 for wall mounting see typelist







Date: 2023 03 15 Page 9 of 15

PCE / ELCEE / SIROX / METECEE

13561 Rated current: 63 A 3P+N+PE IP 44 for wall mounting see typelist

3331 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE **IP 44** straight design see typelist

3341 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 straight design see typelist

PCE / ELCEE / SIROX / METECEE 3351

Rated current: 63 A 3P+N+PE IP 44 straight design see typelist

33351 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE **IP 44** straight design see typelist

PCE / ELCEE / SIROX / METECEE 33361

Rated current: 63 A 2P+PE IP 44 straight design see typelist

33451 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE **IP 44** straight design see typelist



within the scope as given in the official decree and published under https://akkreditierung-austria.gv.at.





Date: 2023 03 15 Page 10 of 15

33461 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 straight design see typelist

33551 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 straight design see typelist

33561 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 straight design see typelist

4331 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 sloping design see typelist

4341 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 sloping design see typelist

4351 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 sloping design see typelist

43351 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 sloping design see typelist







Date: 2023 03 15 Page 11 of 15

43361 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 sloping design see typelist

43451 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 sloping design see typelist

43461 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 sloping design see typelist

43551 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 sloping design see typelist

43561 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 sloping design see typelist

13371 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 for wall mounting see typelist

13471 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 for wall mounting see typelist







Date: 2023 03 15 Page 12 of 15

13571 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 for wall mounting see typelist

133751 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 for wall mounting see typelist

133761 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 for wall mounting see typelist

134751 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 for wall mounting see typelist

134761 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 for wall mounting see typelist

135751 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 for wall mounting see typelist

135761 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 for wall mounting see typelist







Certificate No.: 43-152-16 Date: 2023 03 15 Page 13 of 15

| 1 | 3 | 5 | 7 | 5 | 1 | ı . | - | 6 | * | V | m | 1 | | | |
|---|---|----------|---|---|---------------------|-------|-------------|---------------------|---|---|---|-----------------|---|--|--|
| | | | | | | | | | | | | Lid axis | | | |
| | | | | | | | | | | | | blank | made of PC/ABS | | |
| | | | | | | | | | | | | m | made of brass (nickel-plated) | | |
| | | | | | | | | | | | | Contac | ts | | |
| | | | | | | | | | | L | | blank | uncoated contacts | | |
| | | | | | | | | | | | | V | nickel plated contacts | | |
| | | | | | | | | | | | | Colour | | | |
| | | | | | | | | | | | | blank | standard type | | |
| | | | | | | | | | | | | XS | Midnight series | | |
| | | | | | | | | | | | | * | reserved for additional colours | | |
| | | | | | | | | | | | | Clock r | position earthing contact | | |
| | | | | | | | | <u> </u> | | | | 1 | 1 h | | |
| | | | | | | | | | | | | 2 | 2 h | | |
| | | | | | | | | | | | | 3 | 3 h | | |
| | | | | | | | | | | | | 4 | 4 h | | |
| | | | | | | | | | | | | 5 | 5 h | | |
| | | | | | | | | | | | | 6 | 6 h | | |
| | | | | | | | | | | | | 7 | 7 h | | |
| | | | | | | | | | | | | 9 | 8 h (not available in 4- and 5-poles) 9 h | | |
| | | | | | | | | | | | | 10 | 10 h | | |
| | | | | | | | | | | | | 11 | 11 h | | |
| | | | | | | | | | | | | 12 | 12 h | | |
| | | | | | | | | | | | | | ner type | | |
| | | | | | | | <u> </u> | | | | | - | Trademark PCE | | |
| | | | | | | | | | | | | Dagge | Degree of protection | | |
| | | | | | ļ | | | | | | | blank | IP67 or IP66/IP67 | | |
| | | | | | | | | | | | | 1 | IP44 | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | Pilot co | | | |
| | | | | | | | | | | | | blank 5 | without pilot contact with pilot contact | | |
| | | | | | | | | | | | | 6 | with PCS system | | |
| | | | | | | | | | | | | | · | | |
| | | | L | | | | | | | | | Housin blank | g (only for series 13) housing H170 x W118 | | |
| | | | | | | | | | | | | 7 | housing H262 x W 162 | | |
| | | | | | | | | | | | | Poles | | | |
| | | <u> </u> | | | | | | | | | | 3 | 3-poles | | |
| | | | | | | | | | | | | 4 | 4-poles | | |
| | | | | | | | | | | | | 5 | 5-poles | | |
| | | | | | | | | | | | | | | | |
| | | | | | Rated current 3 63A | | | | | | | | | | |
| | | | | | | | Ground type | | | | | | | | |
| | | | | | | | 1 | Wall mounted socket | | | | | | | |
| | | | | | | | | | | | | 3 | Flanged socket straight | | |
| | | | | | | | | | | | | 4 | Flanged socket sloping | | |
| | | | | | | | | | | | | | | | |

OVE Certification





Certificate No.: 43-152-16 Date: 2023 03 15

Page 14 of 15

Typelist

| Туре | Rated current A | Earthing contact pos. | Rated operating voltage V | Frequency Hz | Insulation voltage V |
|-----------------------------|-----------------------|-----------------------|--------------------------------------|-----------------------------|----------------------------|
| 333 433 | | 1 2 | Other ratings >50 | Other ratings >300 - 500 | 500*), 690 500*), 690 |
| 133 | | 3 | >50 – 250 | DC | 500*), 690 |
| 1337 | | 4 | 100 – 130 | 50 and 60 | 500*), 690 |
| 3335 | | 6 | 200 – 250 | 50 and 60 | 500*), 690 |
| 4335 | 00 | 7 | 480 – 500 | 50 and 60 | 500*), 690 |
| 1335 | 63 | 8**) | >250 | DC | 500*), 690 |
| 13375 | | 9 | 380 – 415 | 50 and 60 | 500*), 690 |
| 3336*) | | 10 | >50 | >100 - 300 | 500*), 690 |
| 4336*) 1336*) 13376*) | | 12 | Supply from an isolating transformer | 50 and 60 | 500*), 690 |
| 334 | | 1 | Other ratings | Other ratings | 500*), 690 |
| 434 | | 2 | >50 | >300 - 500 | 500*), 690 |
| 134 | | 3 | 380 | 50 | 500*), 690 |
| 1347 | | | 440 | 60 | |
| 3345 | | 4 | 100 – 130 | 50 and 60 | 500*), 690 |
| 4345 | | 5 | 600 – 690 | 50 and 60 | 690 |
| 1345 | 63 | 6 | 380 – 415 | 50 and 60 | 500*), 690 |
| 13475 | | 7 | 480 - 500 | 50 and 60 | 500*), 690 |
| 3346*) | | 9 | 200 – 250 | 50 and 60 | 500*), 690 |
| 4346*) | | 10 | >50 | >100 - 300 | 500*), 690 |
| 1346*) | | 11 12 | 440 – 460 | 60 | 500*), 690 |
| 13476 [*]) | | 12 | Supply from an isolating transformer | 50 and 60 | 500*), 690 |
| 335 | | 1 | Other ratings | Other ratings | 500*), 690 |
| 435 | | 2 | >50 | >300 - 500 | 500*), 690 |
| 135 1357 | | 3 | 220/380 250/440 | 50 60 | 500*), 690 |
| | | 4 | 57/100 – 75/130 | 50 and 60 | 500*), 690 |
| 3355 4355 | | 5 | 347/600 – 400/690 | 50 and 60 | 690 |
| 4355 1355 | 63 | 6 | 200/346 – 240/415 | 50 and 60 | 500*), 690 |
| 13575 | | 7 | 277/480 – 288/500 | 50 and 60 | 500*), 690 |
| 3356*) | | 9 | 120/208 – 144/250 | 50 and 60 | 500*), 690 |
| 4356*) | | 10 | >50 | >100 - 300 | 500*), 690 |
| 1356*) | | 11 | 250/440 – 265/460 | 60 | 500*), 690 |
| 13576*) | | 12 | Supply from an isolating transformer | 50 and 60 | 500*), 690 |

^{*)} Types 1336, 13376, 3336, 4336, 1346, 13476, 3346, 4346, 1356, 13576, 3356, 4356 with insulation voltage 500 V and with add. marking: "Only for use with electrical interlock"





^{**)} Earthing contact position 8h > 250V DC only for types 1335, 13375, 3335, 4335, 1336, 13376, 3336, 4336 with add. marking: "Only for use with electrical interlock"



Certificate No.: 43-152-16 Date: 2023 03 15

Page 15 of 15

Typelist

| Туре | Rated current A | Earthing contact pos. | Rated operating voltage V | Frequency Hz | Insulation voltage V |
|---------------------|-----------------------|-----------------------|----------------------------|-----------------|----------------------------|
| 3331 | | 1 | Other ratings | Other ratings | 500*), 690 |
| 4331 | | 2 | >50 | >300 - 500 | 500*), 690 |
| 1331 | | 3 | >50 – 250 | DC | 500*), 690 |
| 13371 | | 4 | 100 – 130 | 50 and 60 | 500*), 690 |
| 33351 | | 6 | 200 – 250 | 50 and 60 | 500*), 690 |
| 43351 | 63 | 7 | 480 – 500 | 50 and 60 | 500*), 690 |
| 13351 | 03 | 8**) | >250 | DC | 500*), 690 |
| 133751 | | 9 | 380 – 415 | 50 and 60 | 500*), 690 |
| 33361*) | | 10 | >50 | >100 - 300 | 500*), 690 |
| 43361*) | | 12 | Supply from an | 50 and 60 | 500*), 690 |
| 13361*) 133761*) | | | isolating transformer | | |
| | | 1 | Other ratings | Other ratings | 500*), 690 |
| 3341 | | 2 | >50 | >300 - 500 | 500*), 690 |
| 4341 1341 | | 3 | 380 | 50 | 500*), 690 |
| 1341 | | | 440 | 60 | ,, |
| | | 4 | 100 – 130 | 50 and 60 | 500*), 690 |
| 33451 | | 5 | 600 – 690 | 50 and 60 | 690 |
| 43451 | 63 | 6 | 380 – 415 | 50 and 60 | 500*), 690 |
| 13451 134751 | | 7 | 480 - 500 | 50 and 60 | 500*), 690 |
| | | 9 | 200 – 250 | 50 and 60 | 500*), 690 |
| 33461*) | | 10 | >50 | >100 - 300 | 500*), 690 |
| 43461*) | | 11 | 440 – 460 | 60 | 500*), 690 |
| 13461*) | | 12 | Supply from an | 50 and 60 | 500*), 690 |
| 134761*) | | | isolating transformer | | · |
| 3351 | | 1 | Other ratings | Other ratings | 500*), 690 |
| 4351 | | 2 | >50 | >300 - 500 | 500*), 690 |
| 1351 | | 3 | 220/380 | 50 60 | 500*), 690 |
| 13571 | | 4 | 250/440 57/100 – 75/130 | 50 and 60 | 500*), 690 |
| 33551 | 63 | 5 | 347/600 – 400/690 | 50 and 60 | 690 |
| 43551 | | 6 | 200/346 – 240/415 | 50 and 60 | 500*), 690 |
| 13551 | | 7 | 277/480 – 288/500 | 50 and 60 | 500*), 690 |
| 135751 | | 9 | 120/208 – 144/250 | 50 and 60 | 500*), 690 |
| 33561*) | | 10 | >50 | >100 - 300 | 500*), 690 |
| 43561*) | | 11 | 250/440 – 265/460 | 60 | 500*), 690 |
| 13561*) | | 12 | Supply from an | 50 and 60 | 500*), 690 |
| 135761*) | | 12 | isolating transformer | Jo and Jo | 300), 090 |

^{*)} Types 13361, 133761, 33361, 43361, 13461, 134761, 33461, 43461, 13561, 135761, 33561, 43561 with insulation voltage 500 V and with add. marking: "Only for use with electrical interlock"





^{**)} Earthing contact position 8h > 250V DC only for types 13351, 133751, 33351, 43351, 13361, 133761, 33361, 43361 with add. marking: "Only for use with electrical interlock"