OVE Austrian Electrotechnical Association

Eschenbachgasse 9 | 1010 Wien | Austria ZVR: 327279890 | www.ove.at

OVE Certification

Kahlenberger Str. 2A | 1190 Wien | Austria T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at



Page 1 of 9

ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark



Certificate No.: 43-155-15 Valid from: 2023 01 12

until: 2025 01 12

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Company: PC Electric Ges.m.b.H.

Diesseits 145

4973 St. Martin im Innkreis

Austria

Product: Socket outlets for industrial purposes

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s):: 3694-1853/22

Österreichischer Verband für Elektrotechnik

Head of OVE Certification


Digitally signed by T. Neumayer Email=t neumayer@ove.at

Dipl.-Ing. T. Neumayer



Wien, 2023 01 12









Date: 2023 01 12 Page 2 of 9

Manufacturer:

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Factory location(s):

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01 ÖVE/ÖNORM EN 60309-2:2013-03-01 EN IEC 60309-1:2022 EN IEC 60309-2:2022 IEC 60309-1:2021 IEC 60309-2:2021

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

Product: Socket outlets for industrial purposes

Type designation: Trademark:

Rating:

3432P+PE
IP 67 or IP 66/IP 67

Rated insulation voltage: 690 V without pilot contact straight flange see typelist

344 PCE / ELCEE / SIROX / METECEE

IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V without pilot contact straight flange see typelist

OVE Certification

3P+PE





Date: 2023 01 12

Page 3 of 9

PCE / ELCEE / SIROX / METECEE 345

3P+N+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V without pilot contact straight flange see typelist

3435 PCE / ELCEE / SIROX / METECEE

2P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with pilot contact straight flange

see typelist

PCE / ELCEE / SIROX / METECEE 3445

3P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with pilot contact straight Flange see typelist

3455 PCE / ELCEE / SIROX / METECEE

3P+N+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with pilot contact straight flange see typelist

PCE / ELCEE / SIROX / METECEE 3436

2P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with PCS-system straight flange see typelist

PCE / ELCEE / SIROX / METECEE 3446

3P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with PCS-system straight flange see typelist





Date: 2023 01 12 Page 4 of 9

3456 PCE / ELCEE / SIROX / METECEE

3P+N+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with PCS-system straight flange see typelist

443 PCE / ELCEE / SIROX / METECEE

2P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V without pilot contact sloping flange see typelist

444 PCE / ELCEE / SIROX / METECEE

3P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V without pilot contact sloping flange see typelist

445 PCE / ELCEE / SIROX / METECEE

3P+N+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V without pilot contact sloping flange see typelist

4435 PCE / ELCEE / SIROX / METECEE

2P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with pilot contact sloping flange see typelist

4445 PCE / ELCEE / SIROX / METECEE

3P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with pilot contact sloping flange see typelist





Date: 2023 01 12 Page 5 of 9

4455 PCE / ELCEE / SIROX / METECEE

3P+N+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with pilot contact sloping flange see typelist

4436 PCE / ELCEE / SIROX / METECEE

2P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with PCS-system sloping flange see typelist

4446 PCE / ELCEE / SIROX / METECEE

3P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with PCS-system sloping flange see typelist

4456 PCE / ELCEE / SIROX / METECEE

3P+N+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with PCS-system sloping flange see typelist

143 PCE / ELCEE / SIROX / METECEE

2P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V without pilot contact for wall mouting see typelist

144 PCE / ELCEE / SIROX / METECEE

3P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V without pilot contact for wall mounting siehe typelist





Date: 2023 01 12 Page 6 of 9

PCE / ELCEE / SIROX / METECEE 145

3P+N+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V without pilot contact for wall mounting

1435 PCE / ELCEE / SIROX / METECEE 2P+PE

IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V

with pilot contact for wall mounting siehe typelist

see typelist

PCE / ELCEE / SIROX / METECEE 1445

3P+PE IP 67 or IP 66/IP 67

Rated insulation voltage: 690 V with pilot contact for wall mounting see typelist

1455 PCE / ELCEE / SIROX / METECEE

3P+N+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with pilot contact for wall mounting

PCE / ELCEE / SIROX / METECEE 1436

2P+PE

see typelist

IP 67 or IP 66/IP 67

Rated insulation voltage: 690 V

with PCS-system for wall mounting see typelist

PCE / ELCEE / SIROX / METECEE 1446

3P+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with PCS-system for wall mounting see typelist





Date: 2023 01 12 Page 7 of 9

1456 3P+N+PE IP 67 or IP 66/IP 67 Rated insulation voltage: 690 V with PCS-system for wall mounting see typelist PCE / ELCEE / SIROX / METECEE







Date: 2023 01 12 Page 8 of 9

Typelist

Туре	Rated current A	Earthing contact pos. h	Rated operating voltage V	Frequency Hz
143		1	Other ratings	Other ratings
343		2	>50	>300 - 500
443		3	>50 - 250	DC
		4	100 – 130	50 and 60
1435*		6	200 – 250	50 and 60
3435*	125	7	480 – 500	50 and 60
4435*		8	>250	DC
		9	380 – 415	50 and 60
1436*		10	>50	>100 - 300
3436* 4436*		12	Supply from an isolating transformer	50 and 60
		1	Other ratings	Other ratings
144		2	>50	>300 - 500
344		3	380	50
444		3	440	60
		4	100 – 130	50 and 60
1445*		5	600 – 690	50 and 60
3445*	125	6	380 – 415	50 and 60
4445* 1446* 3446* 4446*		7	480 - 500	50 and 60
		9	200 – 250	50 and 60
		10	>50	>100 - 300
		11	440 – 460	60
		12	Supply from an isolating transformer	50 and 60
		1	Other ratings	Other ratings
145 345 445 1455*		2	>50	>300 - 500
		3	220/380 250/440	50 60
		4	57/100 – 75/130	50 and 60
		5	347/600 - 400/690	50 and 60
3455*	125	6	200/346 – 240/415	50 and 60
4455*		7	277/480 – 288/500	50 and 60
		9	120/208 – 144/250	50 and 60
1456*		10	>50	>100 - 300
3456* 4456*		11	250/440 – 265/460	60
		12	Supply from an isolating transformer	50 and 60

^{*} Types 1435, 1436, 1445, 1446, 1455, 1456, 3435, 3436, 3445, 3446, 3455, 3456, 4435, 4436, 4445, 4446, 4455, 4456 only for use with electrical interlock.





Date: 2023 01 12 Page 9 of 9

Typecode

	4	_	-		_	*	*		_	. у	pecode
1	4	5	5	-	6		<u> </u>	<u> r</u>	n		
										Lid axis	
										blank	Made of PC/ABS
										m	Made of brass
							Contacts				
							L			blank	uncoated contacts
										*	Nickel plated contacts
										Colour	
										blank	Standard type
										*	Reserved for additional colours
										Clock p	osition earthing contact
										1	1h
										2	2h
										3	3h
										4	4h
										5	5h
										6	6h
										7	7h
										8	8h
										9	9h
										10	10h
										11	11h
										12	12h
										Custom	er type
										-	PCE
										Pilot co	ntact
										blank	without pilot contact
										5	with pilot contact
										6	with PCS-System
										Poles	
										3	3-poles
										4	4-poles
										5	5-poles
										Rated c	
										4	125 A
							Ground				
										1	Wall mounted socket
										3	Flanged socket straight
										4	Flanged socket sloping

OVE Certification

