

Technique for cable laying and overhead line construction

- Energy cable laying up to 680 kV
- Fibre optic, mini and micro cables
- Cable winding and length measuring
- Overhead line construction up to 110 kV
- Seminars and product instructions



Spare rods D 4,5-11 mm



Spare conduit rod yellow, without reel, highest quality of reinforced fibre rod with PP-covering. On ring with alu guide tip. From diam. 9 with shackle. The core of this rod is reinforced by 27 % additional glass fibres. This leads to a higher pushing stability and also to higher breaking resistance.

Code	Type	D/m	Alu-tip-D	kg
211590	ES 4,5-40	4,5/40	11/M5	1,25
211630	ES 4,5-60	4,5/60	11/M5	1,85
211670	ES 4,5-80	4,5/80	11/M5	2,45
214523	ES 6,5-40	6,5/40	12/M8	2,10
214563	ES 6,5-60	6,5/60	12/M8	3,10
214603	ES 6,5-80	6,5/80	12/M8	4,10
217103	ES 9-40	9,0/40	25/M12	4,70
217163	ES 9-60	9,0/60	25/M12	6,80
217243	ES 9-80	9,0/80	25/M12	9,10
217313	ES 9-100	9,0/100	25/M12	11,30
217373	ES 9-120	9,0/120	25/M12	13,45
223463	ES 11-150	11,0/150	25/M12	24,40
223613	ES 11-200	11,0/200	25/M12	32,40
223763	ES 11-250	11,0/250	25/M12	40,50
223913	ES 11-300	11,0/300	25/M12	48,50