

Technique for cable laying and overhead line construction

- Energy cable laying up to 680 kV
- Fibre optic, mini and micro cables
- Cable winding and length measuring
- Overhead line construction up to 110 kV
- Seminars and product instructions



Conduit rods D 9-11 mm with reel



Conduit rod, highest quality of reinforced fibre rod with PP-covering. For pushing through conduits and pulling-in of winch ropes or light cables. Including guide tip of aluminium D 25/M12 and shackle. On galvanized reel with safety brake. With 2 wheels. The core of this rod is reinforced by 27 % additional glass fibres. This leads to a higher pushing stability and also to higher breaking resistance.

Code	Type	D/m	Alu-tip-D	Reel-D	D-ID	kg
215103	RS 9-40	9,0/40	25/M12	800	to 120	18,10
215163	RS 9-60	9,0/60	25/M12	800	to 120	20,40
215243	RS 9-80	9,0/80	25/M12	800	to 120	22,55
215303	RS 9-100	9,0/100	25/M12	800	to 120	24,80
215363	RS 9-120	9,0/120	25/M12	800	to 120	26,90
215373	RS 9-120	9,0/120	25/M12	1000	to 120	34,70
221463	RS 11-150	11,0/150	25/M12	1000	to 200	45,50
221603	RS 11-200	11,0/200	25/M12	1000	to 200	53,50
221613	RS 11-200	11,0/200	25/M12	1200	to 200	59,00
221763	RS 11-250	11,0/250	25/M12	1200	to 200	67,10
221913	RS 11-300	11,0/300	25/M12	1200	to 200	75,20