

BEGA**50 132**

Wall luminaire for indoor use



Project · Reference number

Date

Product data sheet

Application

Open and free-radiating wall luminaire · indoor
luminaire with hand-blown opal glass and metal
bracket.

The character of the opal glass creates a
smooth and uniform light distribution in the
room.

Product description

Aluminium fitter, finish Colour white
Stainless steel glass holding bolts
Hand-blown opal glass
3 fixing holes $\varnothing$ 6.5 mm
130 x 195 mm spacing
2 cable entries for through-wiring for mains
cable up to $\varnothing$ 10.5 mm max. 3×1.5 [□]
Connection terminal 2.5[□]
Earth conductor connection
LED module for power supply
Suitable for phase angle or phase section
dimming
220-230 V $\sim$ 50/60 Hz
BEGA Thermal Switch®
Temporary thermal shutdown to protect
temperature-sensitive components
Safety class I
 – Safety mark
 – Conformity mark
Weight: 1.2 kg
This product contains light sources of energy
efficiency class(es) F

Lamp

Luminaire connected wattage	14 W
Rated temperature	$t_a = 25^\circ\text{C}$
Ambient temperature	$t_{a \text{ max}} = 25^\circ\text{C}$

50 132 K3

Module designation	LED-1246/930
Colour temperature	3000 K
Colour rendering index	$R_a > 90$
Module luminous flux	1320 lm
Luminaire luminous flux	1158 lm
Luminaire luminous efficiency	82,7 lm/W

Service life · Ambient temperature

Rated temperature $t_a = 25^\circ\text{C}$	
LED module:	80,000 h (L 80 B 50)

Ambient temperature max. $t_a = 25^\circ\text{C}$ (100 %)	
LED module:	80,000 h (L 80 B 50)

