

BEGA**67 547.3**

Table lamp for indoor use

Project · Reference number

Date

Product data sheet

Application

Table lamp · indoor luminaire made of metal base and hand-blown opal glass for free radiating and glare-free light.

Product description

Luminaire made of Aluminium,
finish Polished aluminium
Hand-blown opal glass, with screw neck
Built-in toggle switch
Black cable · 2000 mm, with safety plug
LED power supply unit
220-240 V ~ 50/60 Hz
Safety class I
CE – Conformity mark
Weight: 2.1 kg

Lighting technology

Luminaire data for the DIALux lighting design program for outdoor lighting, street lighting and indoor lighting, as well as luminaire data in EULUMDAT and IES format are available on the BEGA website at www.bega.com.

Lamp

Module connected wattage	13.4 W
Luminaire connected wattage	15 W
Rated temperature	$t_a = 25^\circ\text{C}$
Service life criteria	50 000 h / L ₇₀

67 547.3 K3

Colour temperature	3000 K
Colour rendering index	CRI > 85
Module luminous flux	960 lm
Luminaire luminous flux*	800 lm
Luminaire luminous efficiency*	53,3 lm/W

67 547.3 K4

Colour temperature	4000 K
Colour rendering index	CRI > 85
Module luminous flux	1055 lm
Luminaire luminous flux*	880 lm
Luminaire luminous efficiency*	58,7 lm/W

* preliminary data

Article No. 67 547.3

LED colour temperature optionally 3000K or 4000K
3000 K – Article number + **K3**
4000 K – Article number + **K4**

