

Product data sheet

Specifications



Sedna Design & Elements, Key card Switch 10AX, aluminium

SDD113121

Main

Range	Sedna
Function	Card switch
Device application	Key-card switch
Delivery form	Mechanism with fixing frame
Colour	Aluminium
Colour code	RAL 9006

Complementary

	Hotel card switch
Installation	Flush
Power range	2300 W
Rated current	10 AX at 250 V AC
Kind of terminals	Screwless terminals
Terminal capacity	2 cable(s) 2.5 mm²
Wire structure	Flexible Rigid
Wire stripping length	13 mm
Material of visible parts	Thermoplastic ABS-UV stabilised
Surface finish	Painted
Fixing mode	Claws, span of claws working range: 51...70 mm Claws, span of claws working range: 52...68 mm Screws
Height	73 mm
Width	73 mm
Depth	42 mm
Depth of visual part	24 mm
Net weight	0.064 kg

Environment

IP degree of protection	IP20
Conformity mark	CE

Product certifications	GOST-R
------------------------	--------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	7.0 cm
Package 1 Length	9.5 cm
Package 1 Weight	71.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	18.5 cm
Package 2 Length	27.5 cm
Package 2 Weight	791.0 g
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Height	30.0 cm
Package 3 Width	40.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	10.147 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)