



Triple socket-outlet, Mureva Styl, 2P + E with shutters, side earth, 16A, 250V, surface, grey

MUR36038

| V | ı | a | ı | ı | Į |
|---|---|---|---|---|---|
| | | | | | |

| Range | Mureva Styl |
|-----------------------------|------------------|
| Range of product | Mureva Styl |
| Product or component type | Socket-outlet |
| Device presentation | Complete product |
| Outlet poles configuration | 2P + E |
| Outlet standard description | Side earth |
| Outlet standard | Schuko |
| Colour tint | Grey (RAL 7016) |

Complementary

| Device mounting | Surface |
|--|---|
| Socket number | 3 |
| Rated current | 16 A |
| [Ue] rated operational voltage | 250 V AC |
| Condition of use | Indoor/outdoor |
| Material | PC (polycarbonate) Brass PP (polypropylene) |
| Fixing mode | By screws |
| Clamping connection capacity | 12.5 mm² for rigid cable(s) 12.5 mm² for stranded cable(s) 12.5 mm² for flexible cable(s) |
| Wire stripping length | 13 mm |
| Cable entry | Easy valve access diameter: 612 mm |
| Height | 76 mm |
| Width | 218 mm |
| Depth | 64 mm |
| Chemical and detergent products resistance | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A Lactic Acid |

Resistant to A-Lactic Acid

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to diluted quaternary ammonium

Resistant to hydrogen peroxide 10 volumes

Environment

| Quality labels | EAC AENOR |
|---------------------------------------|---|
| IP degree of protection | IP55 |
| IK degree of protection | IK08 |
| Flame retardance | Self-extinguishing 650 °C conforming to IEC 60695-2-1 |
| Ambient air temperature for operation | -540 °C |
| Ambient air temperature for storage | -2555 °C |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.6 cm |
| Package 1 Width | 5.7 cm |
| Package 1 Length | 21.8 cm |
| Package 1 Weight | 369 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 2 |
| Package 2 Height | 8 cm |
| Package 2 Width | 16 cm |
| Package 2 Length | 39.5 cm |
| Package 2 Weight | 830 g |
| Unit Type of Package 3 | S04 |
| Number of Units in Package 3 | 12 |
| Package 3 Height | 30 cm |
| Package 3 Width | 40 cm |
| Package 3 Length | 60 cm |
| Package 3 Weight | 5.846 kg |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|--|
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Recommended replacement(s)