

Technique for cable laying and overhead line construction

- Energy cable laying up to 680 kV
- Fibre optic, mini and micro cables
- Cable winding and length measuring
- Overhead line construction up to 110 kV
- Seminars and product instructions



Cable pulling grips, 1 loop, for 3 cables



Cable pulling grips for 3 cables with 1 loop, galvanized Bowden wire. All Vetter cable grips are handmade therefore of high flexibility. They adapt easy at any difference in cable diameter and are therefore simple to handle. For pulling-in together of 3 single core cables.

- L1 = the lengths without cables in. L2 = total length included the loops.
- The real length mounted on the cable can be much shorter, depending on the cable diameter.
- Loops without thimbles
- B = internal diameter of the loop
- D = thickness of the loop
- kN = minimum breaking load

Code	Type	C-D	B	D	kN	L1/L2	kg
245860	K 30/3	3x25-30	40	13	48,6	1000/1150	0,97
245870	K 40/3	3x30-40	40	13	70,2	1250/1400	1,51
245880	K 50/3	3x40-50	40	13	96,0	1250/1400	2,00
245890	K 60/3	3x50-60	40	13	96,0	1500/1650	2,34
245900	K 70/3	3x60-70	40	13	128,0	1500/1650	2,50