



**ETI-1221** is an electronic thermostat with variable temperature differentials, an independent control relay, and DIN rail - mounted contacts built-in panel.

The thermostat is designed for pipe tracing of high-temperature industrial lines temperature and other heating systems control. The thermostat has an applicable sensor (\*) **ETF 144/99** or **ETF-622**, it depends on controlled temperature requirements. Both sensors can be prolonged with a 100 m cable.

EHF CE

#### TECHNICAL DATA

Voltage	230 V AC 50/60 Hz
Max load	10 A / 2200 W
Temperature range	+10 °C ... +110 °C
Hysteresis	+/-0,4 °C
Setback mode	0,5...10 °C
Sensor type (selected*)	NTC
Heating off in case of sensor's defect	Yes
Light indicator	LED
Dimensions	86x36x58 mm
Protection class	IP20
Warranty	3 year

#### PRODUCT LIST

Type	Temperature range	Sensor	Order No.
ETI 1221	+10 °C ... +110 °C	External	19113680
Sensor ETF 144/99A**	-20 °C ... +70 °C	External	19121438
Sensor ETF 622**	-40 °C ... +120 °C	External	19121436

**\*\*the sensor is supplied additionally**

#### ACCESSORIES

Sensor ETF 144/99A*	Sensor ETF 622**
	