COMFORT HEAT



ERE C€

Comfort Touch thermostat



The electronic clock thermostat **Comfort Touch**, with a fine LCD display, comes with a floor temperature sensor and energy consumption management system.

Comfort Touch thermostat has pre-programmed functions adjusted to Lithuanian climate and weekly mode. Factory settings and data are retrieved beyond power failure.

The thermostat is a wall-mounted into a standard recessed box. Energy consumption management system informs of percentage consumption of adjusted temperature levels, what your monthly consumption is, and upcoming year's expenditure.

TECHNICAL DATA

Voltage	100-240 V AC 50/60 Hz		
Max load	16 A / 3600 W		
Screen	2", 176x220 points, touch screen		
On / off switch	Built-in interrupter 2 pole		
Standby mode energy consumption	< 0,5 W		
Temperature range	+5 °C +40 °C		
Hysteresis	0,4 °C		
Energy consumption and saved time memory	5 year		
	Unlimited time		
Saved programming	Unlimited time		
Saved programming Sensor type	Unlimited time Floor (NTC) and room		
. 5			
Sensor type	Floor (NTC) and room		
Sensor type Sensor resistance	Floor (NTC) and room 14,8 kOhm at 20 °C		
Sensor type Sensor resistance Dimensions	Floor (NTC) and room 14,8 kOhm at 20 °C 84x84x40 mm		

PRODUCT LIST

Туре	Temperature range	Sensor	Order No.	Model
Comfort Touch White	+5 °C +40 °C	Floor and room, 3m	19115967	Elko
Comfort Touch Black	+5 °C +40 °C	Floor and room, 3m	19115968	Elko

WIRING DIAGRAM

