

ENSTO

Pole fuse switch disconnecter

SZ400.322

Code	SZ400.322
GTIN	6438100328726
Name	Pole fuse switch disconnecter 400 A, Al/Cu 2x(50-240) mm ² , poles 3
Description	For protecting stranded overhead cables and underground cables in LV networks. Fuse switch can be operated from the ground level by using operating rods.
Vendor	Ensto Finland Oy



Technical specification

Certificates

Standards:	IEC 60947-1, IEC 60947-3
------------	--------------------------

Features

Connectors included:	3xKG43.6
Number of poles:	3
Utilization category:	AC22B

Others

ETIM Class:	EC001040
-------------	----------

Dimensions

Weight:	10.6 kg
---------	---------

ETIM Technical specification

etim

Max. rated operation voltage Ue AC:	500 V
Rated permanent current Iu:	400 A
Suitable for fuses:	NH2
Number of poles:	3
Type of electrical connection of main circuit:	Cable clamp
Type of control element:	Long turning handle

Packaging

Carton (Default package)

Package size:	1 pce
Depth:	499 mm
Width:	344 mm
Height:	426 mm
Weight:	11.454 kg
Volume:	73.125456 l

Pallet package

Package size:	10 pcs
Depth:	1200 mm
Width:	800 mm
Height:	877 mm
Weight:	134.54 kg
Volume:	841.92 l