



Ledinaire High-bay

BY021P G2 LED205S/840 PSU WB GR

- Power supply unit (ON/OFF) - Beam angle 90° - 90°

The Ledinaire highbay range contains a selection of off-the-shelf highbay LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable. Ledinaire highbay enables, simple and flexible installation, either on a hook, or optional bracket. Products can be installed with optional reflectors for lower glare.

Product data

General Information	
Light source replaceable	Yes
Number of gear units	1 unit
Driver included	Yes
Service tag	No
Lighting Technology	LED
Value ladder	Value
Light Technical	
Luminous Flux	20,500 lumen
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	122 lm/W
Color rendering index (CRI)	>80
Light source color	840 neutral white
Optic type	Wide beam
Luminaire light beam spread	90°
Unified glare rating CEN	Not applicable
Operating and Electrical	
Input Voltage	220 to 240 V

Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Power Consumption	168 W
Inrush current	54 A
Inrush time	0.75 ms
Power Factor (Fraction)	0.9
Connection	Connection unit 3-pole
Cable	Cable 0.3 m with connector 3-pole
Number of products on MCB of 16 A type B	6
Temperature	
Ambient temperature range	-20 to +45 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Constant light output	No

Ledinaire High-bay

Mechanical and Housing	
Housing Material	Aluminium die-cast ADC1 - alloy grade (EN AC-47100)
Reflector material	Aluminum
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Housing Color	Dark gray
Optical cover/lens finish	Matte
Overall height	93 mm
Overall diameter	355 mm

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Sustainability rating	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	Yes
ENEC mark	-
Warranty period	3 years
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

Init. Corr. Color Temperature	4000 K
Initial chromaticity	(0.38, 0.38) SDCM <5
Power consumption tolerance	+/-10%


Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life	7.5 %
50000 h	
Lumen maintenance at median useful life*	L65
50000 h	

Application Conditions	
Performance ambient temperature Tq	35 °C
Suitable for random switching	No

Product Data	
Full product code	871951452404000
Order product name	BY021P G2 LED205S/840 PSU WB GR
EAN/UPC - Product	8719514524040
Order code	911401642307
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material number (12NC)	911401642307
Full product name	BY021P G2 LED205S/840 PSU WB GR
EAN/UPC - Case	8719514524040



Dimensional drawing



Ledinaire High-bay

