



Ledinaire Waterproof WT065C

WT065C G3 LED48S/840 PSU L1200 BN

- 840 neutral white - Power supply unit

The Ledinaire Waterproof range provides maximum performance and durability at great value. As an off-the-shelf LED luminaire solution for all your everyday needs, it can be deployed in a wide variety of locations.

Product data

| General Information | | | |
|--|---|------------------------------------|--|
| Light source color | 840 neutral white | Photobiological risk | Photobiological risk group 0 @200mm to EN62778 |
| Light source replaceable | Yes | Photobiological risk specification | 0.2 m |
| Number of gear units | 1 unit | EU RoHS compliant | Yes |
| Driver/power unit/transformer | Power supply unit (ON/OFF) | Service tag | No |
| Driver included | Yes | Unified glare rating CEN | 31 |
| Optic type | Symmetrical | Lighting Technology | LED |
| Luminaire light beam spread | 110° | Brand | Philips |
| Connection | Push-in connector 3-pole | Value ladder | Value |
| Cable | - | | |
| Protection class IEC | Safety class I | Light Technical | |
| Glow-wire test | Temperature 850 °C, duration 30 s | Luminous Flux | 4,800 lumen |
| Flammability mark | For mounting on normally flammable surfaces | Saturated Red (R9) | <50 |
| CE mark | CE mark | Luminous Efficacy (rated) (Nom) | 109 lm/W |
| ENEC mark | - | Color rendering index (CRI) | >80 |
| Warranty period | 3 years | Flickering value (PstLM) | 1 |
| Constant light output | No | Stroboscopic effect value (SVM) | 2 |
| Number of products on MCB of 16 A type B | 45 | | |

Ledinaire Waterproof WT065C

| | |
|--------------------------|--------------|
| Operating and Electrical | |
| Input Voltage | 220 to 240 V |
| Line Frequency | 50 or 60 Hz |
| Input Frequency | 50 or 60 Hz |
| Power Consumption | 44 W |
| Inrush current | 5.56 A |
| Inrush time | 0.047 ms |
| Power Factor (Fraction) | 0.9 |

| | |
|---------------------------|---------------|
| Temperature | |
| Ambient temperature range | -20 to +40 °C |

| | |
|----------------------|----|
| Controls and Dimming | |
| Dimmable | No |

| | |
|-------------------------------------|--------------------|
| Mechanical and Housing | |
| Housing Material | Polycarbonate |
| Reflector material | - |
| Optic material | Polycarbonate |
| Optical cover/lens material | Polycarbonate |
| Fixation material | Stainless steel |
| Housing Color | Gray |
| Optical cover/lens finish | Opal |
| Overall length | 1,207 mm |
| Overall width | 71 mm |
| Overall height | 74 mm |
| Dimensions (Height x Width x Depth) | NaN x NaN x NaN mm |

| | |
|------------------------------|--|
| Approval and Application | |
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK08 [5 J vandal-protected] |

| | |
|-----------------------|---|
| Sustainability rating | - |
|-----------------------|---|

| | |
|-------------------------------------|--------------------|
| Initial Performance (IEC Compliant) | |
| Luminous flux tolerance | +/-10% |
| Init. Corr. Color Temperature | 4000 K |
| Initial chromaticity | (0.38,0.38) SDCM≤6 |
| Power consumption tolerance | +/-10% |


| | |
|---|-------|
| Over Time Performance (IEC Compliant) | |
| Control gear failure rate at median useful life | 7.5 % |
| 50000 h | |
| Lumen maintenance at median useful life* | 70 |
| 50000 h | |

| | |
|------------------------------------|-------|
| Application Conditions | |
| Performance ambient temperature Tq | 25 °C |
| Suitable for random switching | Yes |

| | |
|---------------------------------|-----------------------------------|
| Product Data | |
| Full product code | 871951496383299 |
| Order product name | WT065C G3 LED48S/840 PSU L1200 BN |
| Order code | 911401807685 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 9 |
| Material number (12NC) | 911401807685 |
| Net weight | 1.120 kg |
| Full product name | WT065C G3 LED48S/840 PSU L1200 BN |
| EAN/UPC - Case | 8719514963917 |



Dimensional drawing



Ledinaire Waterproof WT065C

