



Ledinaire Waterproof

WT060C LED56S/840 PSU TW1 L1500

- 840 neutral white - Power supply unit (ON/OFF)

The Ledinaire waterproof (WT060) range contains a selection of popular off-the-shelf waterproof LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable. Ledinaire enables, simple and quick installation, with optional through wiring possibility.

Product data

General Information	
Beam angle of light source	120 degree(s)
Light source color	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit (ON/OFF)
Driver included	Yes
Optic type	Symmetrical
Luminaire light beam spread	120°
Control interface	-
Connection	Connection unit 3-pole
Cable	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	10

EU RoHS compliant	Yes
Service tag	No
Unified glare rating CEN	Not applicable
Lighting Technology	LED
Brand	Philips
Value ladder	Value

Light Technical	
Luminous Flux	5,600 lumen
Luminous Efficacy (rated) (Nom)	120 lm/W
Color rendering index (CRI)	>80
Flickering value (PstLM)	1
Stroboscopic effect value (SVM)	1.6

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W


Ledinaire Waterproof

Power Consumption	46 W
Inrush current	3.3 A
Inrush time	0.115 ms
Power Factor (Fraction)	0.9
Temperature	
Ambient temperature range	-20 to +45 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Polycarbonate
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Stainless steel
Housing Color	Gray and white
Optical cover/lens finish	Opal
Overall length	1,558 mm
Overall width	69 mm
Overall height	59 mm
Dimensions (Height x Width x Depth)	NaN x NaN x NaN mm
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Sustainability rating	-

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Init. Corr. Color Temperature	4000 K
Initial chromaticity	<5
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life	7.5 %
50000 h	
Lumen maintenance at median useful life*	L70
50000 h	
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes
Product Data	
Full product code	871016336012699
Order product name	WT060C LED56S/840 PSU TW1 L1500
Order code	911401876980
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	911401876980
Net weight	1.000 kg
Full product name	WT060C LED56S/840 PSU TW1 L1500
EAN/UPC - Case	8710163360249



Dimensional drawing



Ledinaire Waterproof

