



Ledinaire floodlights gen3

BVP164 LED60/840 PSU 50W SWB CE

- - - 840 neutral white - - - Symmetrical

This Ledinaire floodlights range contains a selection of popular off-the-shelf LED luminaires that comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

Product data

General Information	
Lamp family code	-
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Light source engine type	LED
Service tag	No
Lighting Technology	LED
Light Technical	
Upward light output ratio	0
Luminous Flux	6,000 lumen
Standard tilt angle posttop	-
Standard tilt angle side entry	-
Luminous Efficacy (rated) (Nom)	120 lm/W
Color rendering index (CRI)	>80
Light source color	840 neutral white
Optical cover/lens type	Glass
Luminaire light beam spread	110° x 110°

Optic type outdoor	Symmetrical
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	50 W
Power Consumption	50 W
End CLO power consumption	- W
Inrush current	1.68 A
Inrush time	0.0082 ms
Power Factor (Fraction)	0.95
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug
Number of products on MCB of 16 A type B	44


Ledinaire floodlights gen3

Temperature	
Ambient temperature range	-25 to +40 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	-
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Housing Color	Gray
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	173 mm
Overall width	232 mm
Overall height	26.1 mm
Effective projected area	0.028 m²
Dimensions (Height x Width x Depth)	NaN x NaN x NaN mm
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge Protection (Common/Differential)	2/2 kV
Sustainability rating	-
Protection class IEC	Safety class I
Flammability mark	-
CE mark	Yes
ENEC mark	-
Warranty period	3 years

Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Init. Corr. Color Temperature	4000 K
Initial chromaticity	(0.380, 0.380) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	80
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Product Data	
Full product code	871951453353099
Order product name	BVP164 LED60/840 PSU 50W SWB CE
Order code	911401854483
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16
Material number (12NC)	911401854483
Net weight	0.850 kg
Full product name	BVP164 LED60/840 PSU 50W SWB CE
EAN/UPC - Case	8719514533776



Dimensional drawing



Ledinaire floodlights gen3

