Product data sheet Characteristics

MTN3115-0000

Two-circuit switch insert 1 pole, flush-mounted, 10 AX, AC 250 V, screwl. term.





Main

		ī
Range of product	Merten inserts	
Product or component type	Switch	
Device presentation	Mechanism	

Complementary

Switch function	1-pole 1-way	<u> </u>
Actuator	Rocker	
Device mounting	Flush	- 0
Fixing mode	By screws and claws	
[Ue] rated operational voltage	250 V	
Rated current	10 AX	
Maximum switching current	10 A	7
Number of rocker	2	-
Pilot light	Red indicator	***
Connections - terminals	Screwless terminals	ž
Material	Metal Plastic	, y
		To the state of th

Environment

IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	62 g	
Package 1 Height	3.7 cm	

Package 1 width	7.1 cm
Package 1 Length	7.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	730 g
Package 2 Height	18 cm
Package 2 width	9 cm
Package 2 Length	27 cm
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Weight	4.87 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
Cradle to Cradle	Bronze ☐	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Marranti	10 months
Warranty	18 months
	TO MONUTO