



Main

Range	Linergy
Product name	FT
Device short name	GV2G
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	3P
Range compatibility	TeSys D TeSys GV2 TeSys K TeSys U
Number of tap-offs	2
[Ith] conventional free air thermal current	63 A
Connection pitch	45 mm

Complementary

Mounting location	On terminal
[Ui] rated insulation voltage	690 V
Length	89 mm
Net weight	0.036 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	38 g
Package 1 Height	2 cm
Package 1 width	4 cm

Package 1 Length	9.5 cm
Unit Type of Package 2	S01
Number of Units in Package 2	100
Package 2 Weight	3.787 kg
Package 2 Height	15 cm
Package 2 width	15 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	3200
Package 3 Weight	130.9 kg
Package 3 Height	77 cm
Package 3 width	60 cm
Package 3 Length	80 cm


Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile


Contractual warranty

Warranty	12 months
----------	-----------

Sets of Busbars GV2G... with Terminal Block GV1G09



Sets of Busbars GV2G245, GV2G254, GV2GR272



	I
GV2G245 (2 x 45 mm)	89
GV2G254 (2 x 54 mm)	98
GV2G272 (2 x 72 mm)	116