



## Main

|                                    |                      |
|------------------------------------|----------------------|
| Range                              | Resi9                |
| Product or component type          | Comb busbar          |
| Accessory / separate part category | Connection accessory |
| Lines description                  | 3L                   |
| Length in 18 mm modules            | 12                   |

## Complementary

|                                |                                                     |
|--------------------------------|-----------------------------------------------------|
| Number of ways                 | 4 ways 3 L                                          |
| Poles configuration for 1 way  | 1 x 3P                                              |
| Connection pitch               | 18 mm                                               |
| Connector type                 | Fork                                                |
| Distance between way           | 54 mm                                               |
| Marking                        | L1 L2 L3                                            |
| Insulation                     | Insulated                                           |
| Device presentation            | Cuttable                                            |
| [Ie] rated operational current | 63 A at 40 °C                                       |
| [Ue] rated operational voltage | 400 V AC Ph/Ph                                      |
| [Ui] rated insulation voltage  | 500 V AC                                            |
| Mounting mode                  | Horizontal                                          |
| Mounting location              | Bottom on biconnect                                 |
| 9 mm pitches                   | 24                                                  |
| Width                          | 220 mm                                              |
| Colour                         | White (RAL 9003)                                    |
| Range compatibility            | Acti 9 K60<br>Resi9 MCB<br>Resi9 RCBO<br>Resi9 RCCB |

## Environment

|                        |                                             |
|------------------------|---------------------------------------------|
| Standards              | IEC 60947-7-1<br>IEC 61439-2                |
| Product certifications | CE                                          |
| Fire resistance        | 960 °C ( 30 s ) conforming to IEC 60695-2-1 |
| Pollution degree       | 3                                           |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Weight             | 82 g      |
| Package 1 Height             | 2.8 cm    |
| Package 1 width              | 21.7 cm   |
| Package 1 Length             | 1.7 cm    |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 5         |
| Package 2 Weight             | 480 g     |
| Package 2 Height             | 5.6 cm    |
| Package 2 width              | 25 cm     |
| Package 2 Length             | 8.8 cm    |
| Unit Type of Package 3       | S04       |
| Number of Units in Package 3 | 195       |
| Package 3 Weight             | 19.865 kg |
| Package 3 Height             | 30 cm     |
| Package 3 width              | 40 cm     |
| Package 3 Length             | 60 cm     |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                 |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|