Product data sheet Characteristics

ISM20808 OptiLine 45 OptiLine 70 - foot - grey



Cabling installation system	Pole	
Product or component type	Foot	— ;

Complementary

Complementary		
Type of pole	One-sided Two-sided	alorite fr
Colour tint	Grey (RAL 9007)	
Quantity per set	Set of 1	£
Pole/Post surface finish	Anodized Powder coated	e ile
Pole fixing mode	Free-standing	
Fixing mode	Free-standing	<u> </u>
Material	Cast iron painted	
Height	29 mm	
Diameter	317 mm	
Market segment	Small commercial Residential	2010 604
		y

Environment

Ambient air temperature for operation	-2560 °C	- 6
IP degree of protection	IP30	-ţ

Packing Units

Number of Units in Package 1 1 Package 1 Weight 10.824 kg Package 1 Height 2.9 cm Package 1 width 31.7 cm Package 1 Length 31.7 cm	Unit Type of Package 1	PCE	
Package 1 Height 2.9 cm Package 1 width 31.7 cm	Number of Units in Package 1	1	
Package 1 width 31.7 cm	Package 1 Weight	10.824 kg	
	Package 1 Height	2.9 cm	
Package 1 Length 31.7 cm	Package 1 width	31.7 cm	
	Package 1 Length	31.7 cm	

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months