Product data sheet Characteristics

NSYS3D3215P

Spacial S3D plain door with mount.plate. H300xW200xD150 IP66 IK10 RAL7035.





Main

IVIAIII		9
Range	Spacial	,
Product name	Spacial S3D	
Application	Multi-purpose	
Category	Compact enclosure	
Enclosure nominal height	300 mm	
Enclosure nominal width	200 mm	
Enclosure nominal depth	150 mm	
Door type	Plain	
Mounting plate description	Plain	
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Device composition	evice composition 1 body 1 mounting plate 1 door with lock 1 cable gland plate	

Complementary

Body type	Single piece body Gutter-shaped front rail double sheet thickness	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 mm double-bar lock	
Accessibility for operation	for operation Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure: steel Mounting plate: galvanised steel	

Surface finish	Enclosure: epoxy-polyester powder	
Colour	Enclosure: grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	LR	
	UL	
	BV	
	GL	
	DNV	
	CUL	
Net weight	3.58 kg	

Environment

IK degree of protection	IK10 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529

Packing Units

1
3.59 kg
19.5 cm
21 cm
31 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
alifornia proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds is known to the State of California to cause cancer and birth defects or other reproductive h more information go to www.P65Warnings.ca.gov		

Contractual warranty

	-	
Warranty	18 month	S
•		