Product data sheet Characteristics

MGN15717

fuse-disconnector SBI - 3 poles - 125 A - for fuse 22 x 58 mm



Acti 9	
Acti 9 SBI	
Fuse-disconnector	
SBI	
3P	
	Acti 9 SBI Fuse-disconnector SBI

Complementary

Complementary		
[In] rated current	32 A	
	40 A	<u></u>
	50 A	:: :: :: ::
	63 A	2
	80 A	<u>}</u>
	100 A	suifa Hilith
	125 A	
Fuse curve	GG	
	AM	<u> </u>
Fuse size	22 x 58 mm	
[Ue] rated operational voltage	690 V AC	
Mounting support	35 mm symmetrical DIN rail	9
9 mm pitches	12	<u></u>
Connections - terminals	Screw clamp terminals1 cable(s) 2.525 mm² rigid	. <u>u</u>
	Screw clamp terminals1 cable(s) 2.525 mm² flexible	ā
Tightening torque	3.5 N.m	

Environment

Standards	IEC EN 60947-3	_ anded
Pollution degree	3	— ştri
Ambient air temperature for operation	-2060 °C	c
Ambient air temperature for storage	-4080 °C	

Packing Units

racking Office	
Unit Type of Package 1	PCE

Number of Units in Package 1	1
Package 1 Weight	554 g
Package 1 Height	7.7 cm
Package 1 width	10.5 cm
Package 1 Length	12.8 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	2
Package 2 Weight	1.178 kg
Package 2 Height	8 cm
Package 2 width	13 cm
Package 2 Length	22 cm
Unit Type of Package 3	S03
Number of Units in Package 3	18
Package 3 Weight	11.089 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months