



Main

Range	Wibe
Product name	Wibe Cable Ladders
Product or component type	Cable ladder
Device short name	KHZSP
Device application	Dry environment

Complementary

Type of side profile	Open profile
Type of rung	Perforated profile
Mounting location	Indoor
Rung spacing	250 mm
Material with surface treatment	Steel, pre-galvanized
Corrosion class	C2
Height	55 mm
Width	300 mm
Length	4 m
Net weight	217 kg / 100 m

Environment

Mounting location	Partly outdoor environment with low exposure to corrosion ware-houses and parking garages
Standards	IEC 61537

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	7.98 kg

Package 1 Height	5.5 cm
Package 1 width	29.8 cm
Package 1 Length	400 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------