



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCKD XCKP XCKT XCMD
Associated body	ZCMD41L1 ZCMD29L2 ZCD29M12 ZCP26 ZCP29 ZCMD41L5 ZCMD39L2 ZCT27P16 ZCMD69C12 ZCMD25L1 ZCMD61C12 ZCP31 ZCMD37L5 ZCMD81L2 ZCT25P16 ZCD25 ZCT26P16 ZCMD21L08R12 ZCT25N12 ZCT26N12 ZCD21 ZCT21P16 ZCMD81L5 ZCD37 ZCT25G11 ZCP39 ZCMD29C12 ZCT28P16

ZCP21M12
 ZCT26G11
 ZCD27
 ZCMD25L5
 ZCP21
 ZCP37
 ZCD28
 ZCMD21L2
 ZCMD21L08U78
 ZCT21G11
 ZCP25
 ZCT21N12
 ZCMD37L1
 ZCD39
 ZCMD61M12
 ZCT28N12
 ZCMD25L2
 ZCD29
 ZCD35
 ZCMD81L1
 ZCT28G11
 ZCMD21C12
 ZCMD29L5
 ZCMD21L1
 ZCMD21M12
 ZCMD39L5
 ZCP35
 ZCMD37L2
 ZCD21M12
 ZCT27G11
 ZCMD21L5
 ZCP27
 ZCP28
 ZCMD39L1
 ZCD26
 ZCT27N12
 ZCMD41L2
 ZCD31
 ZCMD29L1
 ZCP29M12

Movement of operating head	Linear
Type of operator	Roller plunger spring return metal
Type of approach	Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	10 g
Package 1 Height	0.594 cm
Package 1 width	1.579 cm
Package 1 Length	2.945 cm

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	12 months
----------	-----------