

PHILIPS

Lighting



HF-Performer II for PL-T/C/R/L/TL5C lamps

HF-P 2 22-42 PL-T/C/L/TL5C EII 220-240V

HF-Performer EII PL-T/C/R/T5c is a sustainable, slim and high-frequency electronic ballast for a wide range of CFL- ni applications. It is ideal for applications where high energy efficiency is required. The HF-Performer EII range has a robust design, meets all relevant international safety and performance standards and is energy-efficient (CELM A A2). The ballast is primarily designed for Indoor application. For outdoor application, the luminaire should be minimum Classland need to be sufficiently protected against water & dust. The installation should also be guard against any lightening surge or any other necessary electrical protection as deemed in such typical installation & application.

Product data

General Information		Wiring	
Number of Lamps	2 piece/unit	Connector Type Input Terminals	Insert
Connector Type Output Terminals		Connector Type Output Terminals	Insert
Operating and Electrical		Temperature	
Input Voltage	220 to 240 V	Ambient temperature range	-25 °C to 50 °C
Line Frequency	50 to 60 Hz	T-Case Lifetime (Nom)	75 °C
Input Frequency	50 to 60 Hz	T-Case Maximum (Max)	75 °C
Inrush Current Width	0.35 ms		
Inrush Current Peak (Max)	31 A		
Number of Products on MCB (16A Type B)	12		
(Nom)			
Approval and Application			
Ingress protection code		IP20 [Finger-protected]	
Energy Efficiency Index		A2	
Safety Standard		IEC 61347-2-3	

HF-Performer II for PL-T/C/R/L/TL5C lamps

Environmental Standard	ISO 14001
Approval Marks	CE marking ENEC certificate VDE-EMV certificate
Product Data	
Full product code	871150091399930
Order product name	HF-P 2 22-42 PL-T/C/L/TL5C EII 220-240V
Order code	913700630866

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	913700630866
Full product name	HF-P 2 22-42 PL-T/C/L/TL5C EII 220-240V
EAN/UPC - Case	8711500914019



Dimensional drawing

Product	D1	C1	A1	A2	B1	B2
HF-P 2 22-42 PL-T/C/L/ TL5C EII 220-240V	4.5 mm	30.0 mm	103.0 mm	93.5 mm	67.0 mm	57.5 mm

