

## PD-C 360i/8 DUO DALI

### Item number

EP10427442

### GTIN

4015120427442



|       |      |      |      |      |      |
|-------|------|------|------|------|------|
| Ø 8 m | 360° | DALI | IP20 | 2 CH | 2 CH |
|-------|------|------|------|------|------|

### Product description

- Presence detector with **360° field of detection** for ceiling mounting
- **Range of up to 8 m** in the diameter at a recommended installation height of 3 m
- Automatic light control by DALI or DALI-2 control gear to a **constant brightness level** depending on presence and daylight

### Offers special product features like:

- Presence and daylight dependent constant light control
- Simple parameterisation, remote control and documentation with ESY-Pen and ESY-App
- Broadcast control of DALI and DALI-2 control gear



### Technical data

#### GENERAL

|                      |  |
|----------------------|--|
| Device category      | Ceiling-mounted presence detector  |
| Product information  | Broadcast control of DALI and DALI-2 control gear<br>Mounting position: Keep a safe distance of 5 m from radio antennas (e.g. WiFi access points). |
| Included in delivery | Includes lens mask   |
| User interface       | IR remote control with "blue mode" technology  |
| Remote controllable  | ✓  |
| Conformity           | CE, EAC, RoHS, WEEE  |
| Warranty             | 5 years  |

#### ATTACHMENT

|                                |                                     |
|--------------------------------|-------------------------------------|
| Installation type              | Flush-mounted/Device socket Ø 68 mm |
| Installation position          | Ceiling                             |
| Installation dimension         | Installation depth: 24 mm, Ø 60 mm  |
| Type of connection             | Push terminal                       |
| Connectable wire cross section | 1.5 – 2.5 mm <sup>2</sup>           |

#### HOUSING

|                                 |  |
|---------------------------------|--|
| Dimensions                      | Height/Depth 62 mm, Ø 108 mm                     |
| Weight                          | 134 g  |
| Material                        | UV-stabilised polycarbonate                      |
| Protection type                 | IP20   |
| Protection type with accessory  | IP54 with surface-mounted box (order separately) |
| Permissible ambient temperature | -25 °C...+50 °C                                  |
| Relative humidity               | 5 - 93 %, non-condensing                         |
| Colour                          | white, similar to RAL 9010                       |

#### ELECTRICAL VERSION

|                |      |
|----------------|------|
| Control system | DALI |
|----------------|------|

|                   |                 |
|-------------------|-----------------|
| Protection class  | II              |
| Nominal voltage   | 230 V ~ / 50 Hz |
| Output current    | 100 mA          |
| Power consumption | 0.6 W           |

#### SENSORS

|                                 |                         |
|---------------------------------|-------------------------|
| Detection angle                 | 360°                    |
| Detection range diagonally      | Ø 8 m                   |
| Detection range head-on         | Ø 6 m                   |
| Detection range presence        | Ø 4 m                   |
| Field of detection              | up to 50 m <sup>2</sup> |
| Recommended installation height | 3 m                     |
| Max. mounting height            | 5 m                     |
| Light measurement               | mixed light             |
| Level of brightness             | 100 - 2000 lx           |

#### CHANNELS (LIGHTING / HVAC)

|                                      |   |
|--------------------------------------|---|
| Number of light channels             | 2                                       |
| Number of HVAC-channels              | 2                                       |
| Push button input lighting           | 2                                       |
| Push button input HVAC               | -                                       |
| Slave input                          | ✓                                       |
| Mode                                 | Semi-automatic, Fully automatic         |
| Switching delay from "dark to light" | 300 s                                   |
| Switching delay from "light to dark" | 30 s                                    |
| Constant light control               | ✓                                       |
| Sensitivity configurable             | ✓                                       |
| Channel                              | C1 Lighting                             |
| Function                             | Switching, Regulate, Dimming, Broadcast |

## PD-C 360i/8 DUO DALI

|                    |               |
|--------------------|---------------|
| <b>Item number</b> | <b>GTIN</b>   |
| EP10427442         | 4015120427442 |

|  |   |
|--|---|
| Switch contact                           | Bus system, 50 mA, max. 25 driver       |
| Push button input                        | ✓                                       |
| Impulse mode                             | -                                       |
| Switch-off delay time                    | 60 s...240 min (adjustable in steps)    |
| Orientation light                        | 10 - 50 % luminous efficiency           |
| Switch-off delay time, orientation light | 60 s...240 min                          |
| Channel                                  | <b>C2</b> Lighting                      |
| Function                                 | Switching, Regulate, Dimming, Broadcast |
| Switch contact                           | Bus system, 50 mA, max. 25 driver       |
| Push button input                        | ✓                                       |
| Switch-off delay time                    | 60 s...240 min (adjustable in steps)    |
| Orientation light                        | 10 - 50 % luminous efficiency           |
| Switch-off delay time, orientation light | 60 s...240 min                          |

|                       |   |
|-----------------------|---|
| Channel               | <b>C3</b> with accessory (ACTUATOR FULL AUTO C3 DALI) |
| Function              | Switching   |
| Switching capacity    | 10 A (12 V DC / 230 V AC)                             |
| Switch contact        | make contact / floating                               |
| Push button input     | ✓   |
| Switch-off delay time | 60 s...120 min (adjustable in steps)                  |
| Channel               | <b>C4</b> with accessory (ACTUATOR SEMI AUTO C4 DALI) |
| Function              | Switching   |
| Switching capacity    | 10 A (12 V DC / 230 V AC)                             |
| Switch contact        | make contact / floating                               |
| Push button input     | ✓   |
| Switch-off delay time | 60 s...120 min (adjustable in steps)                  |

### Factory settings

|  |                    |
|--|--------------------|
| <b>GENERAL</b>                             |                    |
| Sensitivity                                | 100 %              |
| Afterglow luminous efficiency              | 10 %               |
| Afterglow duration                         | 1 min              |
| Orientation light ON                       | -                  |
| Orientation light, depending on brightness | ✓                  |
| Switching threshold for orientation light  | 500 lx             |
| Deviation (%)                              | 0 %                |
| Luminous efficiency switch-on value        | 10 %               |
| <b>CHANNELS (LIGHTING / HVAC)</b>          |                    |
| Channel                                    | <b>C1</b> Lighting |

|  |                    |
|--|--------------------|
| Operating mode                           | fully automatic    |
| Level of brightness/switching threshold  | 500 lx             |
| Switch-off delay time                    | 5 min              |
| Luminous efficiency of orientation light | 10 %               |
| Duration of switch-off warning           | 300 s              |
| Channel                                  | <b>C2</b> Lighting |
| Operating mode                           | Semi-automatic     |
| Level of brightness/switching threshold  | 500 lx             |
| Switch-off delay time                    | 5 min              |
| Luminous efficiency of orientation light | 10 %               |
| Duration of switch-off warning           | 300 s              |

### Accessories

| Product designation                      | Item number | Product description  | GTIN          |
|--|-------------|--|---------------|
| <b>Ceiling-mounted presence detector</b> |             |  |               |
| PD-C 360/8 Slave                         | EP10055379  | Slave presence detector for extending the field of detection of a Master presence detector   | 4015120055379 |
| PD-C 360/24 Slave                        | EP10055386  | Slave presence detector for extending the field of detection of a Master presence detector   | 4015120055386 |
| PD-C 360/32 Slave                        | EP10427770  | Slave presence detector for extending the field of detection of a Master presence detector   | 4015120427770 |
| <b>Cover</b>                             |             |  |               |
| COMPACT COVER SET 8 SR                   | EP10425936  | Cover set for COMPACT series, 8 m, consists of cover and design ring, stainless steel appearance, similar to RAL 9006                      | 4015120425936 |
| COMPACT COVER SET 8 BK                   | EP00007521  | Cover set for COMPACT series, 8 m, consists of cover and design ring, black  | 4015120007521 |
| <b>Electrical accessories</b>            |             |  |               |
| ACTUATOR FULL AUTO C3 DALI               | EP10427473  | Modul for the conversion of bus commands from the DALI presence detector and other light controls into switching signals (fully automatic) | 4015120427473 |
| ACTUATOR SEMI AUTO C4 DALI               | EP10427480  | Modul for the conversion of bus commands from the DALI presence detector and other light controls into switching signals (semi-automatic)  | 4015120427480 |


## PD-C 360i/8 DUO DALI

| Item number | GTIN          |
|-------------|---------------|
| EP10427442  | 4015120427442 |


### Accessories

| Product designation                 | Item number | Product description  | GTIN          |
|-------------------------------------|-------------|--|---------------|
| <b>Mounting</b>                     |             |  |               |
| COMPACT MOUNTING BOX IP20 SM WH     | EP10425370  | Surface-mounted box for COMPACT series, IP20, white  | 4015120425370 |
| COMPACT MOUNTING BOX IP20 SM SR     | EP10425387  | Surface-mounted box for COMPACT series, IP20, silver   | 4015120425387 |
| COMPACT MOUNTING BOX IP54 SM WH     | EP10425905  | Surface-mounted box for COMPACT series, IP54, white  | 4015120425905 |
| COMPACT MOUNTING BOX IP54 SM SR     | EP10425912  | Surface-mounted box for COMPACT series, IP54, silver   | 4015120425912 |
| MOUNTING SET IP20 FM 62 WH          | EP10425929  | Recessed ceiling mounting set includes installation bracket and dust-protected box, 62 mm  | 4015120425929 |
| COMPACT MOUNTING BOX IP54 SM BK     | EP10426940  | Surface-mounted box for COMPACT series, IP54, black  | 4015120426940 |
| COMPACT MOUNTING BOX IP20 SM BK     | EP10426933  | Surface-mounted box for COMPACT series, IP20, black  | 4015120426933 |
| COMPACT APC MOUNTING BOX IP20 SM WH | EP10426278  | Surface-mounted box IP20 for COMPACT APC DALI-2  | 4015120426278 |
| <b>Protection</b>                   |             |  |               |
| BASKET GUARD ROUND LARGE            | EM10425608  | Basket guard for presence and motion detectors and smoke detectors, Ø 180 mm, height 90 mm   | 4015120425608 |
| BASKET GUARD ROUND SMALL            | EM10425615  | Basket guard for presence and motion detectors and smoke detectors, Ø 165 mm, height 70 mm   | 4015120425615 |
| <b>Remote control</b>               |             |  |               |
| ESY-Pen                             | EP10425356  | ESY-Pen and ESY-App, two tools for every task: (1) Parameterisation, (2) remote control, (3) light measurement, (4) project management | 4015120425356 |
| REMOTE CONTROL PDi DALI             | EP10425899  | IR remote control for DALI presence detectors and motion detectors   | 4015120425899 |
| REMOTE CONTROL PDi/USER             | EM10425547  | IR remote control for end users of presence detectors  | 4015120425547 |

### Dimension drawing



### Field of detections




### Detection range

|                   |       |
|-------------------|-------|
| Diagonally (A)    | Ø 8 m |
| Frontal (B)       | Ø 6 m |
| Presence area (C) | Ø 4 m |

## PD-C 360i/8 DUO DALI

**Item number**      **GTIN**  
 EP10427442      4015120427442

### Circuit diagram



Standard operation with optional control via a closing button and use of max. ten slave devices to one master device.

### Detailed product description

- Presence detector with **360° field of detection** for ceiling mounting
- **Range of up to 8 m** in the diameter at a recommended installation height of 3 m
- Automatic light control by DALI or DALI-2 control gear to a **constant brightness level** depending on presence and daylight
- Default settings ensure immediate operability
- Simple programming using remote control with "blue mode" technology
- Remote control can be deactivated (sabotage protection)
- Additional push button input per channel
- Detector can be used as a fully automatic or semi-automatic device
- Lowering of the luminous efficiency after expiration of the time setting for use as an orientation light for hallways and passageways, adjustable between 10 - 50%
- Integrated switch-off warning
- Flush-mounted device as standard
- Surface mounting or recessed ceiling mounting with accessories
- Easily replaceable/paintable cover and design ring (available in "silver" as an accessory)
- Field of detection can be extended by connecting slave devices
- Targeted masking out of areas by means of an enclosed lens mask