



Main

| | |
|--------------------------------|-------------------------|
| Range of product | Acti9 |
| Product name | Acti9 iCT |
| Product or component type | Contactor |
| Device short name | ICT |
| Device application | Motor-heating-lighting |
| Poles | 2P |
| [Ie] rated operational current | 16 A AC-7A 6 A AC-7B |
| Pole contact composition | 1 NO + 1 NC |
| Network type | AC |
| Control type | Remote control |
| [Uc] control circuit voltage | 230...240 V AC 50 Hz |

Complementary

| | |
|--|------------------------------|
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 250 V AC 50 Hz |
| Maximum power | 1.2 W at 250 V AC |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Control signal type | Maintained |
| Switching frequency | 100 switching operations/day |
| Local signalling | Action indicator |
| Hold-in power consumption in VA | 2.7 VA |
| Inrush power in VA | 9.2 VA |
| Mounting mode | Clip-on |
| Mounting support | 35 mm symmetrical DIN rail |
| 9 mm pitches | 2 |
| Height | 81 mm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------------|--|
| Width | 18 mm |
| Depth | 60 mm |
| Colour | White |
| Mechanical durability | 1000000 cycles |
| Electrical durability | 100000 cycles IEC/EN 61095 16 A 50 Hz AC-7A 30000 cycles IEC/EN 61095 6 A 50 Hz AC-7B 30000 cycles IEC/EN 61095 50 Hz AC-7C 100000 cycles EN/IEC 60947-4-1 50 Hz AC-1 30000 cycles EN/IEC 60947-4-1 50 Hz AC-3 30000 cycles EN/IEC 60947-4-1 50 Hz AC-5a 30000 cycles EN/IEC 60947-4-1 50 Hz AC-5b |
| Connections - terminals | Control circuit: tunnel type terminals2 cable(s) 1.5 mm ² rigid Power circuit: tunnel type terminals1 cable(s) 1...4 mm ² flexible Power circuit: tunnel type terminals1 cable(s) 1.5...6 mm ² rigid Control circuit: tunnel type terminals1 cable(s) 1.5...2.5 mm ² rigid Control circuit: tunnel type terminals2 cable(s) 1.5...2.5 mm ² flexible |
| Tightening torque | Control circuit: 0.8 N.m Power circuit: 0.8 N.m |
| Product compatibility | IACTs |
| Compatibility code | ICT |
| Market segment | Residential Small commercial |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC/EN 61095 |
| Noise level | 30 dB |
| Heat dissipation | 0.9 W at 50/60 Hz |
| IP degree of protection | IP20 |
| Pollution degree | 2 |
| Tropicalisation | 2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095 |
| Relative humidity | 95 % at 55 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -40...70 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 117 g |
| Package 1 Height | 1.8 cm |
| Package 1 width | 6.7 cm |
| Package 1 Length | 8.4 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 12 |
| Package 2 Weight | 1.466 kg |
| Package 2 Height | 3.28 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 20 cm |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 144 |
| Package 3 Weight | 18.142 kg |
| Package 3 Height | 30 cm |
| Package 3 width | 30 cm |
| Package 3 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 12 months |
|----------|-----------|