

# Product datasheet

## Characteristics

# ZCKE21

limit switch head ZCKE - thermoplastic roller lever plunger



## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ21H29 ZCKJ8 ZCKJ7H7 ZCKJ4 ZCKJ2 ZCKJ2H7 ZCKJ41H7 ZCKJ11H29 ZCKJ5H7 ZCKJ41 ZCKJ11H7 ZCKJD37 ZCKJ5 ZCKJ1 ZCKJ2H29 ZCKJ8H29 ZCKJD37H7 ZCKJ6H29 ZCKJ9H29 ZCKJD39H7 ZCKJ7 ZCKJD35H7 ZCKJD35 ZCKJD31H7 ZCKJD39H29 ZCKJ21 ZCKJ4H29 ZCKJD39 ZCKJ1H7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ6H7  
ZCKJD31H29  
ZCKJ1H7  
ZCKJD35H29  
ZCKJ9  
ZCKJ11  
ZCKJ6  
ZCKJ4H7  
ZCKJD37H29  
ZCKJ9H7  
ZCKJ5H29  
ZCKJ41H29  
ZCKJ8H7  
ZCKJD31  
ZCKJ1H29  
ZCKJ7H29

Movement of operating head	Linear Rotary
Type of operator	Roller lever plunger spring return thermoplastic
Type of approach	Lateral approach, 1 direction

#### Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

#### Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	178 g
Package 1 Height	4.4 cm
Package 1 width	5.6 cm
Package 1 Length	6.2 cm

#### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

#### Contractual warranty

Warranty	12 months
----------	-----------