



# Ledinaire Waterproof WT065C

## WT065C LED29\_48S/840 PSU L1200

Ledinaire Waterproof WT065C, All-in, 42 W, 23 W, L1200 mm, 2900 lm, 4800 lm, 4000 K, Symmetrical, Opal, IP65, IK08, TW1-ready

The Ledinaire Waterproof range provides maximum performance and durability at great value. As an off-the-shelf LED luminaire solution for all your everyday needs, it can be deployed in a wide variety of locations.

### Product data

General Information		Operating and Electrical	
Light source replaceable	No	Luminous Efficacy (rated) (Nom)	126 114 lm/W
Number of gear units	1 unit	Color rendering index (CRI)	>80
Driver included	Yes	Light source color	840 neutral white
Service tag	No	Optic type	Symmetrical
Lighting Technology	LED	Luminaire light beam spread	110°
Value ladder	Value	Unified glare rating CEN	31
Serviceability class	Class C, luminaire without serviceable parts, not serviceable	All-in Type	All-in, Multi Lumen
Warranty period	3 years	<b>Operating and Electrical</b>	
Sustainability rating	-	Input Voltage	220 to 240 V
<b>Light Technical</b>		Line Frequency	50 or 60 Hz
Luminous Flux	2,900 4,800 lm	Inrush current	14.2 A
Saturated Red (R9)	<50	Inrush time	0.222 ms
Correlated Color Temperature (Nom)	4000 K	Power Consumption	42 23 W
		Power Factor (Fraction)	0.9
		Connection	Push-in connector 3-pole

# Ledinaire Waterproof WT065C

Cable	-
Number of products on MCB of 16 A type B	36
Suitable for random switching	No
Protection class IEC	Safety class I
Feed-through wiring	Simple Connection and removable cover available for feed-through wiring 1-phase (internal wiring is not included)
Total harmonic distortion	12 %

## Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

## Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Steel
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Stainless steel
Housing Color	Grey
Optical cover finish	Opal
Overall length	1,207 mm
Overall width	71 mm
Overall height	74 mm
Dimensions (Height x Width x Depth)	74 x 71 x 1207 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Net Weight (Piece)	1.150 kg

## Emergency Operation

Central Emergency	No
-------------------	----

## Approval and Application

Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	For mounting on easily flammable surfaces

CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +40 °C

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38,0.38) SDCM≤5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5

## Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L70
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 75000 h	-

## Product Data

Order product name	WT065C LED29_48S/840 PSU L1200
Full product name	WT065C LED29_48S/840 PSU L1200
Full product code	872016950021199
Order code	911401815185
Material Nr. (12NC)	911401815185
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169500211
Numerator - Packs per outer box	9
EAN/UPC - Case	8720169500310

# Ledinaire Waterproof WT065C

## Dimensional drawing

