

PHILIPS**Lighting**

Ledinaire Waterproof WT065C

WT065C G3 LED74S/840 PSU L1500 BN

Ledinaire Waterproof WT065C, (in brown Eco Packaging), 54 W, L1500 mm, 7400 lm, 4000 K, Symmetrical, Opal, IP65, IK08, TW1-ready

The Ledinaire Waterproof range provides maximum performance and durability at great value. As an off-the-shelf LED luminaire solution for all your everyday needs, it can be deployed in a wide variety of locations.

Product data

General Information		Operating and Electrical	
Light source replaceable	Yes	Luminous Efficacy (rated) (Nom)	137 lm/W
Number of gear units	1 unit	Color rendering index (CRI)	>80
Driver included	Yes	Light source color	840 neutral white
Service tag	No	Optic type	Symmetrical
Lighting Technology	LED	Luminaire light beam spread	110°
Value ladder	Value	Unified glare rating CEN	31
Serviceability class	Class C, luminaire without serviceable parts, not serviceable		
Warranty period	3 years	Operating and Electrical	
Sustainability rating	-	Input Voltage	220 to 240 V
		Line Frequency	50 or 60 Hz
		Inrush current	17.2 A
		Inrush time	0.172 ms
		Power Consumption	54 W
		Power Factor (Fraction)	0.9
		Connection	Push-in connector 3-pole
		Cable	-

Ledinaire Waterproof WT065C

Number of products on MCB of 16 A type B	31	ENEC mark	-
Suitable for random switching	No	Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Protection class IEC	Safety class I	Photobiological risk specification	0.2 m
Feed-through wiring	Simple Connection and removable cover available for feed-through wiring 1-phase (internal wiring is not included)	EU RoHS compliant	Yes
Total harmonic distortion	20 %	Performance ambient temperature Tq	25 °C
Controls and Dimming		Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Dimmable	No	Stroboscopic effect visibility measure (SVM)	0.4
Driver/power unit/transformer	Power supply unit (On/Off)	Ambient temperature range	-20 to +40 °C
Control interface	-	Initial Performance (IEC Compliant)	
Constant light output	No	Luminous flux tolerance	+/-10%
Mechanical and Housing		Initial chromaticity	(0.38,0.38) SDCM≤5
Housing Material	Polycarbonate	Power consumption tolerance	+/-10%
Reflector material	Steel	Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5
Optic material	Polycarbonate	Over Time Performance (IEC Compliant)	
Optical cover material	Polycarbonate	Control gear failure rate at median useful life	7.5 %
Fixation material	Stainless steel	50000 h	L70
Housing Color	Grey	Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	
Optical cover finish	Opal	Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 75000 h	-
Overall length	1,507 mm	Product Data	
Overall width	71 mm	Order product name	WT065C G3 LED74S/840 PSU L1500 BN
Overall height	74 mm	Full product name	WT065C G3 LED74S/840 PSU L1500 BN
Dimensions (Height x Width x Depth)	74 x 71 x 1507 mm	Full product code	871951496386399
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]	Order code	911401807985
Mech. impact protection code	IK08 [5 J vandal-protected]	Material Nr. (12NC)	911401807985
Net Weight (Piece)	1.350 kg	Numerator - Quantity Per Pack	1
Emergency Operation		EAN/UPC - Product/Case	8719514963863
Central Emergency	No	Numerator - Packs per outer box	9
Approval and Application		EAN/UPC - Case	8719514963948
Glow-wire test	Temperature 850 °C, duration 30 s		
Flammability mark	For mounting on easily flammable surfaces		
CE mark	Yes		

Ledinaire Waterproof WT065C

Dimensional drawing

