



Ledinaire Waterproof Tube Housing

WT050C 1xTLED L1200

Ledinaire Waterproof Tube Housing, L1200 mm, IP65, IK08

The Ledinaire waterproof (WT050C) range contains a selection of empty, waterproof housings, that can cater for LED tubes of your choice. It comes with the high Philips quality levels at a competitive price. Ledinaire enables, simple and quick installation, with a choice of single and double tube installations.

Product data

General Information		Ingress protection code	
Value ladder	Value	IP65 [Dust penetration-protected, jet-proof]	
Light Technical		Mech. impact protection code	IK08 [5 J vandal-protected]
Color rendering index (CRI)	-	Accessory color	Gray
Luminaire light beam spread	-	Angle	-
Operating and Electrical		Net Weight (Piece)	0.700 kg
Input Voltage	220 to 240 V	Approval and Application	
Line Frequency	50 or 60 Hz	CE mark	Yes
Protection class IEC	Safety class II	EU RoHS compliant	Yes
Mechanical and Housing		Product Data	
Overall length	1,280 mm	Order product name	WT050C 1xTLED L1200
Overall width	69 mm	Full product name	WT050C 1xTLED L1200
Overall height	70 mm	Full product code	871016336602999
Dimensions (Height x Width x Depth)	70 x 69 x 1280 mm	Order code	911401807381
Material	Polycarbonate	Material Nr. (12NC)	911401807381
		Numerator - Quantity Per Pack	1
		EAN/UPC - Product/Case	8710163366029

Ledinaire Waterproof Tube Housing

Numerator - Packs per outer box	12
EAN/UPC - Case	8710163366180

Dimensional drawing

WT050C L1200 1 Tube

