



CorePro GLASS LED candles and lusters

CorePro LEDLusterND6.5-60W P45 E14840CLG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

| General Information | |
|--|--------------------|
| Cap-Base | E14 |
| Nominal lifetime | 15,000 hour(s) |
| Switching Cycle | 20,000 |
| Lighting Technology | LED |
| Flux measurement reference | Sphere |
| Light Technical | |
| Color Code | 840 [CCT of 4000K] |
| Luminous Flux | 806 lm |
| Color Designation | Cool White (CW) |
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 124.00 lm/W |
| Color Consistency | <6 |
| Color rendering index (CRI) | 80 |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % |
| Photobiological safety according to EN 62471 | RG1 |

| Operating and Electrical | |
|---------------------------|-------------|
| Line Frequency | 50 to 60 Hz |
| Input Frequency | 50 to 60 Hz |
| Power Consumption | 6.5 W |
| Lamp Current (Nom) | 50 mA |
| Wattage Equivalent | 60 W |
| Starting Time (Nom) | 0.5 s |
| Warm-up time to 60% light | 0.5 s |
| Power Factor (Fraction) | 0.55 |
| Voltage (Nom) | 220-240 V |
| Temperature | |
| T-Case Maximum (Nom) | 55 °C |
| Controls and Dimming | |
| Dimmable | No |

CorePro GLASS LED candles and lusters

Mechanical and Housing

| | |
|--------------------|----------|
| Bulb Finish | Clear |
| Bulb Shape | P45 |
| Net Weight (Piece) | 0.014 kg |

Approval and Application

| | |
|---|---------|
| Energy Efficiency Class | E |
| Energy Consumption kWh/1000 h | 7 kWh |
| EPREL Registration Number | 1825181 |
| CE mark | Yes |
| EU RoHS compliant | Yes |
| Flickering value (PstLM) - Flickering value as per EN 61000-3-3 | 1 |
| Stroboscopic effect visibility measure (SVM) | 0.9 |


Application Conditions

| | |
|-------------------------------------|----|
| can it be used in closed luminaires | No |
|-------------------------------------|----|

Product Data



| | |
|---------------------------------|--|
| Order product name | CorePro LEDLusterND6.5-60W P45 E14840CLG |
| Full product name | CorePro LEDLusterND6.5-60W P45 E14840CLG |
| Full product code | 871951434758800 |
| Order code | 929002028692 |
| Material Nr. (12NC) | 929002028692 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8719514347588 |
| Numerator - Packs per outer box | 10 |
| EAN/UPC - Case | 8719514347595 |

Dimensional drawing



| Product | D | C |
|--|-------|-------|
| CorePro LEDLusterND6.5-60W P45 E14840CLG | 45 mm | 80 mm |

Photometric data




Light Distribution Diagram - CorePro LEDLusterND6.5-60W P45 E14840CLG

General uniform lighting - CorePro LEDLusterND6.5-60W P45 E14840CLG


CorePro GLASS LED candles and lusters

Photometric data




Spectral Power Distribution Colour - CorePro LEDLusterND6.5-60W P45
E14840CLG

Lifetime



Lumen Maintenance Diagram - CorePro LEDLusterND6.5-60W P45
E14840CLG



Life Expectancy Diagram

